



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Hazardous Substances (Safety Data Sheets) Notice 2017 EPA Consolidation 30
September 2022

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

Section 1: Identification

Product identifier

Product Name BOSTIK 2405 CONTACT ADHESIVE PART A

Other means of identification

Recommended use of the chemical and restrictions on use

Recommended use Contact adhesives

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Supplier

Bostik New Zealand Limited
19 Eastern Hutt Road Wingate,
Lower Hutt, New Zealand
Tel: 04-567 5119
Fax: 04-567 5412

Manufacturer

Bostik New Zealand Limited
19 Eastern Hutt Road Wingate,
Lower Hutt, New Zealand
Tel: 04-567 5119
Fax: 04-567 5412

E-mail address SDS.AP@Bostik.com

Emergency telephone number

Emergency Telephone 24 Hr: 0800 243 622
International +64 4 917 9888
Poison Centre : 0800 764 766

Section 2: Hazard identification

GHS Classification

| | |
|--|------------|
| Flammable liquids | Category 2 |
| Aspiration hazard | Category 1 |
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Reproductive toxicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Hazardous to the aquatic environment - chronic | Category 2 |

Label elements



Signal word
Danger

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

Hazard statements

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves, protective clothing, eye protection and face protection
Wash face, hands and any exposed skin thoroughly after handling
Use only outdoors or in a well-ventilated area
Do not breathe dust
Avoid release to the environment
Ground and bond container and receiving equipment
Use non-sparking tools
Take action to prevent static discharges
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Keep cool
Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Skin

If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Spill

Collect spillage

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

Toxic to aquatic life. In use, may form flammable/explosive vapor-air mixture.

Section 3: Composition/information on ingredients

| Chemical name | CAS No. | Weight-% |
|---------------------|----------|----------|
| Methyl ethyl ketone | 78-93-3 | 20- <40 |
| Toluene | 108-88-3 | 10 - <20 |

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

| Chemical name | CAS No. | Weight-% |
|--------------------|-----------|----------|
| Heptane | 142-82-5 | 10 - <20 |
| Acetone | 67-64-1 | 5 - <10 |
| Cyclohexane | 110-82-7 | 5 - <10 |
| Methylcyclopentane | 96-37-7 | 1 - <3 |
| Octane | 111-65-9 | 1 - <3 |
| Zinc oxide | 1314-13-2 | 0.1- <1 |

| | | |
|---------------------------|-------------|---------|
| Non-hazardous ingredients | Proprietary | Balance |
|---------------------------|-------------|---------|

Section 4: First-aid measures

Description of first aid measures

| | |
|---|--|
| General advice | Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. |
| Inhalation | Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. |
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. |
| Skin contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists. |
| Ingestion | Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention. |
| Self-protection of the first aider | Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing. |

Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| Symptoms | Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. |
| Effects of Exposure | May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility. May cause damage to organs through prolonged or repeated exposure. |

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|---|
| Note to physicians | Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances. |
|---------------------------|---|

Section 5: Fire-fighting measures

Suitable Extinguishing Media

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides. Hydrocarbons. Hydrogen chloride.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Keep from any possible contact with water. Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage

Precautions for safe handling

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials. Keep away from water or moist air.

Recommended storage temperature

Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

Section 8: Exposure controls/personal protection

Working area parameters, subject to mandatory control (MAC or TSEL)

Exposure Limits

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

| Chemical name | New Zealand | ACGIH TLV | United Kingdom | Australia |
|--------------------------------|---|-------------------------------------|---|--|
| Methyl ethyl ketone 78-93-3 | TWA: 150 ppm; TWA: 445 mg/m ³ ; STEL: 300 ppm; STEL: 890 mg/m ³ ; | TWA: 75 ppm STEL: 150 ppm pSk | TWA: 200 ppm; TWA: 600 mg/m ³ ; STEL: 300 ppm; STEL: 899 mg/m ³ ; pSk | TWA: 150 ppm; TWA: 445 mg/m ³ ; STEL: 300 ppm; STEL: 890 mg/m ³ ; |
| Toluene 108-88-3 | TWA: 20 ppm; TWA: 75 mg/m ³ ; STEL: 100 ppm; STEL: 377 mg/m ³ ; dSk | TWA: 20 ppm pOt | TWA: 50 ppm; TWA: 191 mg/m ³ ; STEL: 100 ppm; STEL: 384 mg/m ³ ; pSk | TWA: 50 ppm; TWA: 191 mg/m ³ ; STEL: 150 ppm; STEL: 574 mg/m ³ ; |
| Heptane 142-82-5 | TWA: 400 ppm; TWA: 1640 mg/m ³ ; STEL: 500 ppm; STEL: 2050 mg/m ³ ; | TWA: 400 ppm STEL: 500 ppm | TWA: 500 ppm; TWA: 2085 mg/m ³ ; STEL: 1500 ppm; STEL: 6255 mg/m ³ ; | TWA: 400 ppm; TWA: 1640 mg/m ³ ; STEL: 500 ppm; STEL: 2050 mg/m ³ ; |
| Acetone 67-64-1 | TWA: 500 ppm; TWA: 1185 mg/m ³ ; STEL: 1000 ppm; | TWA: 250 ppm STEL: 500 ppm | TWA: 500 ppm; TWA: 1210 mg/m ³ ; STEL: 1500 ppm; | TWA: 500 ppm; TWA: 1185 mg/m ³ ; STEL: 1000 ppm; |

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

| | | | | |
|-------------------------|--|--|---|---|
| | STEL: 2375 mg/m ³ ; | | STEL: 3620 mg/m ³ ; | STEL: 2375 mg/m ³ ; |
| Cyclohexane 110-82-7 | TWA: 100 ppm; TWA: 350 mg/m ³ ; STEL: 300 ppm; STEL: 1050 mg/m ³ ; | TWA: 100 ppm | TWA: 100 ppm; TWA: 350 mg/m ³ ; STEL: 300 ppm; STEL: 1050 mg/m ³ ; | TWA: 100 ppm; TWA: 350 mg/m ³ ; STEL: 300 ppm; STEL: 1050 mg/m ³ ; |
| Octane 111-65-9 | TWA: 300 ppm; TWA: 1400 mg/m ³ ; STEL: 375 ppm; STEL: 1750 mg/m ³ ; | TWA: 300 ppm | - | TWA: 300 ppm; TWA: 1400 mg/m ³ ; STEL: 375 ppm; STEL: 1750 mg/m ³ ; |
| Zinc oxide 1314-13-2 | TWA: 0.1 mg/m ³ ; respirable dust TWA: 2 mg/m ³ ; respirable dust STEL: 0.5 mg/m ³ ; respirable dust STEL: 5 mg/m ³ ; respirable dust | TWA: 2 mg/m ³ respirable particulate matter STEL: 10 mg/m ³ respirable particulate matter | - | TWA: 10 mg/m ³ ; inhalable dust TWA: 5 mg/m ³ ; fume STEL: 10 mg/m ³ ; fume |

Biological occupational exposure limits

| Chemical name | New Zealand | ACGIH |
|--------------------------------|---|--|
| Methyl ethyl ketone 78-93-3 | 2 mg/L - urine (MEK) - end of shift | 2 mg/L - urine (MEK) - end of shift |
| Toluene 108-88-3 | 0.03 mg/L - urine (Toluene) - end of exposure or end of shift 0.3 mg/g creatinine - urine (O-Cresol) - end of exposure or end of shift | 0.02 mg/L - blood (Toluene) - prior to last shift of workweek 0.03 mg/L - urine (Toluene) - end of shift 0.3 mg/g creatinine - urine (o-Cresol with hydrolysis) - end of shift |
| Acetone 67-64-1 | 50 mg/L - urine (Acetone) - end of shift | 25 mg/L - urine (Acetone) - end of shift |
| Cyclohexane 110-82-7 | - | 50 mg/g creatinine - urine (1,2-Cyclohexanediol) - end of shift at end of workweek |

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Paste Liquid

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

Color Off-white Cream
Odor Solvent.
Odor threshold No information available

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|---|---------------------------|-----------------------------------|
| pH | No data available | Not applicable Insoluble in water |
| Melting point / freezing point | No data available | None known |
| Initial boiling point and boiling range | 50 °C | |
| Flash point | -22 °C | |
| Evaporation rate | No data available | None known |
| Flammability | No data available | Flammable liquid |
| Flammability Limit in Air | | None known |
| Upper flammability or explosive limits | 10 | |
| Lower flammability or explosive limits | 1 | |
| Vapor pressure | <110 kPa | None known |
| Relative vapor density | No data available | None known |
| Relative density | No data available | None known |
| Water solubility | Insoluble in water | |
| Solubility(ies) | No data available | None known |
| Partition coefficient | No data available | None known |
| Autoignition temperature | No data available | None known |
| Decomposition temperature | | None known |
| Kinematic viscosity | No data available | None known |
| Dynamic viscosity | No data available | |
| Explosive properties | No information available. | |
| Oxidizing properties | No information available. | |
| <u>Other information</u> | | |
| Softening point | No information available | |
| Molecular weight | No information available | |
| VOC content | No information available | |
| Density | 0.86 g/cm ³ | |
| Bulk density | No information available | |
| Particle characteristics | | |

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Unstable on exposure to moisture.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Keep from any possible contact with water.

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Carbon oxides.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) >5000 mg/kg
ATEmix (dermal) >5000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-vapor) >20 mg/l
ATEmix (inhalation-dust/mist) 206.60 mg/l

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---------------------|--|---------------------------------------|------------------------------------|
| Methyl ethyl ketone | =2483 mg/kg (Rattus) | = 5000 mg/kg (Oryctolagus cuniculus) | =11700 ppm (Rattus) 4 h |
| Toluene | =5580 mg/kg (Rattus) | = 12000 mg/kg (Oryctolagus cuniculus) | >20 mg/L (Rattus) 4 h |
| Heptane | LD50 > 5000 mg/Kg (rattus) | = 3000 mg/kg (Oryctolagus cuniculus) | =103 g/m ³ (Rattus) 4 h |
| Acetone | =5800 mg/kg (Rattus) 3000 mg/Kg (mouse) | >15800 mg/Kg (Rattus) | =79 mg/l(Rattus) 4 h |
| Cyclohexane | =12705 mg/kg (Rattus) | > 2000 mg/kg (Oryctolagus | >9500 ppm (Rattus) 4 h |

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

| | | | |
|------------|----------------------|---|---|
| | | cuniculus) | |
| Octane | >5000 mg/Kg (Rattus) | - | =118 g/m ³ (Rattus) 4 h = 25260 ppm (Rattus) 4 h > 23.36 mg/L (Rattus) 4 h |
| Zinc oxide | >5000 mg/kg (Rattus) | LD50 >2000 mg/Kg (Rattus) (OECD 402) | LC50 (4h) >5.7 mg/l |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Toluene (108-88-3)

| Method | Species | Exposure route | Effective dose | Exposure time | Results |
|--|---------|----------------|----------------|---------------|----------|
| Regulation (EC) No. 440/2008, Annex, B.4 | Rabbit | Dermal | | | Irritant |

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Component Information
Methyl ethyl ketone (78-93-3)

| Method | Species | Exposure route | Effective dose | Exposure time | Results |
|---|---------|----------------|----------------|---------------|----------|
| OECD Test No. 405: Acute Eye Irritation/Corrosion | Rabbit | eye | | | irritant |

Acetone (67-64-1)

| Method | Species | Exposure route | Effective dose | Exposure time | Results |
|---|---------|----------------|----------------|---------------|----------|
| OECD Test No. 405: Acute Eye Irritation/Corrosion | Rabbit | eye | | | irritant |

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Methyl ethyl ketone (78-93-3)
Toluene (108-88-3)
Acetone (67-64-1)

| Method | Species | Exposure route | Results |
|-------------------------------------|------------|----------------|-----------------------|
| GPMT - Guinea pig maximisation test | Guinea pig | Dermal | Not a skin sensitizer |

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Toluene (108-88-3)

| Method | Species | Results |
|--|------------------------|---------------|
| Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test) | Salmonella typhimurium | Not mutagenic |
| OECD Test No. 476: In Vitro Mammalian Cell Gene Mutation Tests using the Hprt and xprt genes | Mouse | Not mutagenic |

Heptane (142-82-5)

| Method | Species | Results |
|--|---------------|----------------------------|
| OECD Test No. 473: In vitro Mammalian Chromosome Aberration Test | Rat, in vitro | Not mutagenic |
| OECD Test No. 471: Bacterial Reverse Mutation Test | | Not mutagenic in AMES Test |

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

Carcinogenicity

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name | New Zealand | IARC |
|--------------------|-------------|---------|
| Toluene - 108-88-3 | - | Group 3 |

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity

Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.

Toluene (108-88-3)

| Method | Species | Results |
|----------|---------|-----------------------|
| OECD 407 | in vivo | Reproductive toxicant |

STOT - single exposure

May cause drowsiness or dizziness.

Methyl ethyl ketone (78-93-3)

| Method | Species | Exposure route | Effective dose | Exposure time | Results |
|------------------------------|---------|----------------|----------------|---------------|--|
| Experiences made in practice | | | | | May cause drowsiness or dizziness Causes central nervous system depression |

Acetone (67-64-1)

| Method | Species | Exposure route | Effective dose | Exposure time | Results |
|------------------------------|---------|----------------|----------------|---------------|------------------|
| Experiences made in practice | | | | | Narcotic effects |

Narcotic effects

Narcotic effects.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Methyl ethyl ketone (78-93-3)

| Method | Species | Exposure route | Effective dose | Exposure time | Results |
|---|---------|------------------|---------------------------|---------------|----------------|
| OECD Test No. 413: Subchronic Inhalation Toxicity: 90-day Study | Rat | Inhalation vapor | 1254, 2518, 5041 ppm/6h/d | 90 days | NOAEC 5014 ppm |

Toluene (108-88-3)

| Method | Species | Exposure route | Effective dose | Exposure time | Results |
|--|-------------------|-------------------|----------------|---------------|-------------------|
| Regulation (EC) No. 440/2008, Annex, B.26 | Rat, male, female | Oral | | 91 days | NOAEL: 625 mg/kg |
| OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies | Rat, male, female | Inhalation, vapor | | | NOAEL: 1.131 mg/l |

Acetone (67-64-1)

| Method | Species | Exposure route | Effective dose | Exposure time | Results |
|---|---------|----------------|-----------------------|---------------|----------------------------|
| OECD Test No. 408: Repeated Dose 90-Day | Rat | Oral | 200-3400 mg/kg bw/day | 91 days | No Observed Adverse Effect |

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

| | | | | | |
|--------------------------------|-----|------------|-----------|-----------------|---|
| Oral Toxicity Study in Rodents | | | | | Level LOAEL 1700 mg/kg bw/day |
| Not specified | Rat | Inhalation | 19000 ppm | 14, 28, 56 days | NOAEC 19000 ppm No Observed Adverse Effect Level |

Aspiration hazard May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Aquatic ecotoxicity

| Chemical name | Algae/aquatic plants | Fish | Crustacea |
|---------------------|--|---|---|
| Methyl ethyl ketone | EC50=1972 mg/l (Pseudokirchneriella subcapitata) | LC50: 3130 - 3320mg/L (96h, Pimephales promelas) | EC50 48 h > 308 mg/L (Daphnia magna) |
| Toluene | EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata) | LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static) | EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna) |
| Heptane | - | LC50: =375.0mg/L (96h, Cichlid) | EC50: >10mg/L (24h, Daphnia magna) |
| Acetone | - | LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss) | EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static) |
| Cyclohexane | EC50 72 h > 9.3 mg/L (Pseudokirchnerella subcapitata) | LC50: 23.03 - 42.07mg/L (96h, Pimephales promelas) LC50: 48.87 - 68.76mg/L (96h, Poecilia reticulata) LC50: 3.96 - 5.18mg/L (96h, Pimephales promelas) LC50: 24.99 - 44.69mg/L (96h, Lepomis macrochirus) | EC50: >0.9 mg/L (24h, Daphnia magna) |
| Octane | - | - | EC50: =0.38mg/L (48h, Daphnia magna) |
| Zinc oxide | LC 50 (72Hr) 0.136 mg/L | LC50 (96h) =0.7 mg/L (Danio rerio) | LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia) |

Terrestrial ecotoxicity

| Chemical name | Earthworm | Avian | Honeybees |
|---------------|---|---|-----------|
| Acetone | Acute Toxicity: LC50 200 - 1000 µg/cm2 (Eisenia foetida, 48 h filter paper) | Dietary Toxicity: LC50 > 40000 ppm (Phasianus colchicus, 5 Days) Dietary Toxicity: LC50 > 40000 ppm (Coturnix coturnix japonica, 5 Days) | - |

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation

Component Information

| Chemical name | Partition coefficient |
|---------------------|-----------------------|
| Methyl ethyl ketone | 0.3 |
| Toluene | 2.73 |

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

| | |
|-------------|-------|
| Heptane | 4.66 |
| Acetone | -0.24 |
| Cyclohexane | 3.44 |
| Octane | 5.18 |

Mobility in soil

Mobility No information available.

Other adverse effects

No information available.

Disposal methods

Waste from residues/unused products

Dispose of product in packaging in a way that is consistent with the EPA Consolidation 30 April 2021 of the Hazardous Substances (Disposal) Notice 2017 and the Act. Treat the substance using a method that changes the characteristics or composition of the substance so that the substance is no longer a hazardous substance; or export the substance from New Zealand as waste. Flammable substances - may not be disposed of into or onto a landfill or sewage facility.

They may only be burnt in certain situations.

Flammable gases, liquids and solids may only be discharged into the environment or landfill as waste if the substance will not at any time come into contact with any explosives, oxidising gases, liquids or solids or organic peroxides; and there will be no ignition source in the vicinity of the disposal site at any time and if the substance were to ignite, no person, or place where a person may legally be, would be exposed to an unsafe level of heat radiation. Substances which are hazardous to human health or corrosive to metals – may be discharged into the environment if a tolerable exposure limit has been set for the substance (or a component of that substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the tolerable exposure limit. If there is no tolerable exposure limit for the substance, then it may only be discharged into the environment if the substance is very rapidly converted to substances that are not hazardous substances. Environmentally hazardous substances – if the substance, or if it contains a component that is hazardous to the aquatic environment or bioaccumulative and not rapidly degradable, then any component that is bioaccumulative and not rapidly degradable must be removed. The product may only be discharged into the environment if an environmental exposure limit has been set for the substance (or a component of the substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the environmental exposure limit.

Contaminated packaging

For packages that have been in direct contact with hazardous substances, the person must ensure that the package is rendered incapable of containing any substance. It must be disposed of in a manner that is consistent with the requirements for disposal of the substance that it contained, taking into account the material the package is manufactured from. Packages may only be reused or recycled if:

- the substance has a physical hazard other than corrosive to metal, and has been treated to remove any residual contents of the hazardous substance;
- or for substances that have a health or environmental hazard, or corrosive to metal, the contents of the residue in the package are below the threshold for the substance to be classified as hazardous in the Hazardous Substances (Hazard Classification) Notice 2020.

Section 14: Transport information

IATA

UN number or ID number UN1133
UN proper shipping name Adhesives

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

Transport hazard class(es) 3
Packing group II
Special Provisions A3
Description UN1133, Adhesives, 3, II

IMDG

UN number or ID number UN1133
UN proper shipping name Adhesives
Transport hazard class(es) 3
Packing group II
EmS-No. F-E, S-D
Marine pollutant P
Description UN1133, Adhesives, 3, II, (-22°C c.c.), Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

ADR

UN number or ID number UN1133
UN proper shipping name Adhesives
Transport hazard class(es) 3
Labels 3
Packing group II
Description UN1133, Adhesives, 3, II, (D/E), Environmentally Hazardous
Environmental hazards Yes
Limited quantity (LQ) 5 L
Special Provisions 640D
Classification code F1
Tunnel restriction code (D/E)

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EPA New Zealand HSNO approval HSR002662 - Surface Coatings and Colourants (Flammable)
code or group standard

National regulations Any applicable tolerable exposure limits and environmental exposure limits according to the EPA Controls for Hazardous Substances are listed below

| Chemical name | Tolerable Exposure Limit (TEL) Air | Tolerable Exposure Limit (TEL) Water | Tolerable Exposure Limit (TEL) Surface | Environmental Exposure Limits (EEL) |
|-------------------------|------------------------------------|--------------------------------------|--|---|
| Toluene 108-88-3 | 400 µg/m ³ | 0.8 mg/L | - | 330 µg/L (Water) |
| Zinc oxide 1314-13-2 | 0.87 mg/m ³ | 0.6 mg/L | - | 8 µg/L (Freshwater) 15 µg/L (Marine) |

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information
Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information
Controlled substance licenses are required to possess certain explosives, vertebrate toxic agents and fumigants. See Part 7 of the Health and Safety at Work Regulation 2017 for more information

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: Other information

Prepared By Product Safety & Regulatory Affairs
Revision date 02-Apr-2025
Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity
ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| | | | |
|---------|-----------------------------|------|----------------------------------|
| TWA | TWA (time-weighted average) | STEL | STEL (Short Term Exposure Limit) |
| Ceiling | Maximum limit value | Sk* | Skin designation |
| ** | Hazard Designation | + | Sensitizers |
| C | Carcinogen | | |

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program

SAFETY DATA SHEET

BOSTIK 2405 CONTACT ADHESIVE PART A
Revision Number 2

Revision date 02-Apr-2025
Supersedes date 16-Mar-2022

Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet