

# CRC Ceramic Armour Trigger CRC Industries (CRC Industries New Zealand)

Chemwatch: **7918-05** Version No: **3.1** 

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 2

Initial Date: 15/10/2024 Revision Date: 16/10/2024 Print Date: 08/10/2025 S.GHS.NZL.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	RC Ceramic Armour Trigger	
Chemical Name	Not Applicable	
Synonyms	1756338	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Spray on wax for automotive paint protection.
Relevant identified uses	Use according to manufacturer's directions.

#### Details of the manufacturer or importer of the safety data sheet

Registered company name	CRC Industries (CRC Industries New Zealand)	
Address	10 Highbrook Drive East Tamaki Auckland New Zealand	
Telephone	64 9 272 2700	
Fax	+64 9 274 9696	
Website	www.crc.co.nz	
Email	- No EMAL ID NEEDED for NZ - JACK	

# **Emergency telephone number**

Association / Organisation	CRC Industries (CRC Industries New Zealand)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	NZ Poisons Centre 0800 POISON (0800 764 766)	+64 800 700 112 (ID#: 7918-05)
Other emergency telephone number(s)	111 (NZ Emergency Services)	+61 3 9573 3188

# **SECTION 2 Hazards identification**

# Classification of the substance or mixture

Classification <sup>[1]</sup>	Flammable Liquids Category 4, Aspiration Hazard Category 1, Serious Eye Damage/Eye Irritation Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 3	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Determined by Chemwatch using GHS/HSNO criteria	3.1D, 6.1E (aspiration), 6.4A, 9.1C	

#### Label elements

# Hazard pictogram(s)





Signal word	Da	ın	a	е
-------------	----	----	---	---

# Hazard statement(s)

H227	Combustible liquid.	
H304	ay be fatal if swallowed and enters airways.	
H319	Causes serious eye irritation.	
H412	Harmful to aquatic life with long lasting effects.	

# Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P273	Avoid release to the environment.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P264	P264 Wash all exposed external body areas thoroughly after handling.	

# Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.	
P331	Do NOT induce vomiting.	
P370+P378	In case of fire: Use water spray/fog to extinguish.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	

# Precautionary statement(s) Storage

P403	Store in a well-ventilated place.
P405	Store locked up.

# Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

No further product hazard information.

# **SECTION 3 Composition / information on ingredients**

# **Substances**

See section below for composition of Mixtures

#### **Mixtures**

CAS No	%[weight] Name	
64742-48-9.	30-60	naphtha petroleum, heavy, hydrotreated
8015-86-9	1-10	carnauba wax
67762-90-7	1-5	silica, dimethylsiloxane treated
Not Available	balance	Ingredients determined not to be hazardous
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

#### **SECTION 4 First aid measures**

#### Description of first aid measures

Description of first aid mea	asures
Eye Contact	If this product comes in contact with the eyes:  • Wash out immediately with fresh running water.  • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  • Seek medical attention without delay; if pain persists or recurs seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs:  ▶ Immediately remove all contaminated clothing, including footwear.

# ▶ Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. For thermal burns: Decontaminate area around burn. Consider the use of cold packs and topical antibiotics. For first-degree burns (affecting top layer of skin) ▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides. Use compresses if running water is not available. Cover with sterile non-adhesive bandage or clean cloth. ▶ Do NOT apply butter or ointments; this may cause infection. • Give over-the counter pain relievers if pain increases or swelling, redness, fever occur. For second-degree burns (affecting top two layers of skin) ▶ Cool the burn by immerse in cold running water for 10-15 minutes. • Use compresses if running water is not available. ▶ Do NOT apply ice as this may lower body temperature and cause further damage. ▶ Do NOT break blisters or apply butter or ointments; this may cause infection. Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape. To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort): Lay the person flat. Elevate feet about 12 inches. • Elevate burn area above heart level, if possible. Cover the person with coat or blanket. Seek medical assistance. For third-degree burns Seek immediate medical or emergency assistance. In the mean time: Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound. Separate burned toes and fingers with dry, sterile dressings. ▶ Do not soak burn in water or apply ointments or butter; this may cause infection. To prevent shock see above. For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway. Have a person with a facial burn sit up. ▶ Check pulse and breathing to monitor for shock until emergency help arrives. • If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid Inhalation procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Ingestion Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. • Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

#### Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours. Treat symptomatically.

For petroleum distillates

- · In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption decontamination (induced emesis or lavage) is controversial and should be considered on the merits of each individual case; of course the usual precautions of an endotracheal tube should be considered prior to lavage, to prevent aspiration.
- · Individuals intoxicated by petroleum distillates should be hospitalized immediately, with acute and continuing attention to neurologic and cardiopulmonary function.
- · Positive pressure ventilation may be necessary.
- · Acute central nervous system signs and symptoms may result from large ingestions of aspiration-induced hypoxia.
- · After the initial episode,individuals should be followed for changes in blood variables and the delayed appearance of pulmonary oedema and chemical pneumonitis. Such patients should be followed for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated.
- · Gastrointestinal symptoms are usually minor and pathological changes of the liver and kidneys are reported to be uncommon in acute intoxications.
- · Chlorinated and non-chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur. Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

#### **SECTION 5 Firefighting measures**

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

foam.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
----------------------	-------------

#### Advice for firefighters Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Fire Fighting • Prevent, by any means available, spillage from entering drains or water course. • Use water delivered as a fine spray to control fire and cool adjacent area. Combustible. Slight fire hazard when exposed to heat or flame. • Heating may cause expansion or decomposition leading to violent rupture of containers. • On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: Fire/Explosion Hazard carbon dioxide (CO2) nitrogen oxides (NOx) silicon dioxide (SiO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.

#### **SECTION 6 Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> </ul>
Major Spills	Moderate hazard.  ► Clear area of personnel and move upwind.  ► Alert Fire Brigade and tell them location and nature of hazard.  ► Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

# Precautions for safe handling

i recautions for sale name	····g
Safe handling	<ul> <li>Containers, even those that have been emptied, may contain explosive vapours.</li> <li>Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>DO NOT allow clothing wet with material to stay in contact with skin</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> </ul>

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>	
Storage incompatibility	► Avoid strong acids, bases.	

#### **Control parameters**

# Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	naphtha petroleum, heavy, hydrotreated	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	om - Sampled by a method that does not collect vapour
New Zealand Workplace Exposure Standards (WES)	carnauba wax	Respirable dust (not otherwise classified)	3 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	carnauba wax	Inhalable dust (not otherwise classified)	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	silica, dimethylsiloxane treated	Inhalable dust (not otherwise classified)	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	silica, dimethylsiloxane treated	Respirable dust (not otherwise classified)	3 mg/m3	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
naphtha petroleum, heavy, hydrotreated	2,500 mg/m3	Not Available
carnauba wax	Not Available	Not Available
silica, dimethylsiloxane treated	Not Available	Not Available

#### **Exposure controls**

# Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Individual protection measures, such as personal protective equipment









# Eye and face protection

- ▶ Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

# Skin protection

# See Hand protection below

- ► Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

# Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care.

# Body protection

See Other protection below

# Other protection

- Overalls.
- ▶ P.V.C apron.
- ▶ Barrier cream.
- ▶ Skin cleansing cream.

# Recommended material(s)

#### **GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

# Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

**CRC Ceramic Armour Trigger** 

Material	СРІ
BUTYL	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
PVA	С
PVC	С
VITON	С

- \* CPI Chemwatch Performance Index
- A: Best Selection
- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

**NOTE**: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AK-AUS P2	-	AK-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AK-AUS / Class 1 P2	-
up to 100 x ES	-	AK-2 P2	AK-PAPR-2 P2 ^

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

#### **SECTION 9 Physical and chemical properties**

# Information on basic physical and chemical properties

Appearance	White liquid with solvent like odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	1.5
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	10	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>60	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Combustible.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

# Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.		
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.		
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating		
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.		
e) Mutagenicity	Based on available data, the classification criteria are not met.		
f) Carcinogenicity	Based on available data, the classification criteria are not met.		
g) Reproductivity	Based on available data, the classification criteria are not met.		
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.		
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.		
j) Aspiration Hazard	There is sufficient evidence to classify this material as an aspiration hazard		
Inhaled	There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.  Inhalation hazard is increased at higher temperatures.  Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.		
Ingestion	Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)  Accidental ingestion of the material may be damaging to the health of the individual.		
Skin Contact	Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.  There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.  Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.  The material may accentuate any pre-existing dermatitis condition		
Eye	This material causes serious eye irritation.		
Chronic	Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.  There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.  Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  Amorphous silicas generally are less hazardous than crystalline silicas, but the former can be converted to the latter on heating and subsequent cooling. Inhalation of dusts containing crystalline silicas may lead to silicosis, a disabling lung disease that may take years to develop.  Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.  Soluble silicates do not exhibit sensitizing potential. Testing in bacterial and animal experiments have not shown any evidence of them causing mutations or birth defects.  Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS]		

CRC Ceramic Armour	TOXICITY	IRRITATION
Trigger	Not Available	Not Available
naphtha petroleum, heavy, hydrotreated	TOXICITY	IRRITATION
nyuroucuteu	Dermal (rabbit) LD50: >1900 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Inhalation (Rat) LC50: >4.42 mg/L4h <sup>[1]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>
	Oral (Rat) LD50: >4500 mg/kg <sup>[1]</sup>	

carnauba wax	TOXICITY	IRRITATION
Jamada wax	Not Available	Not Available
silica, dimethylsiloxane	TOXICITY	IRRITATION
treated	Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>	Not Available
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.     Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

# NAPHTHA PETROLEUM, HEAVY, HYDROTREATED

Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins.

The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the lipoprotein particles in the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell. Petroleum contains aromatic (benzene, toluene, ethyl benzene, napthalene) and aliphatic hydrocarbons (n-hexane), which can result in many detrimental health effects, including, cancer, tumour formation, hearing loss, and nervous system toxicity. Animal testing shows breathing in petroleum causes tumours of the liver and kidney; these are however not considered to be relevant in humans. Similarly, exposure to gasoline over a lifetime can cause kidney cancer in animals, but the relevance in humans is questionable.

Most studies involving gasoline have shown that gasoline does not cause genetic mutation, including all recent studies in living human subjects (such as in petrol service station attendants).

Animal studies show concentrations of toluene (>0.1%) can cause developmental effects such as lower birth weight and developmental toxicity to the nervous system of the foetus. Other studies show no adverse effects on the foetus. Prolonged contact with petroleum may result in skin inflammation and make the skin more sensitive to irritation and penetration by other materials.

#### **CARNAUBA WAX**

No significant acute toxicological data identified in literature search.

#### SILICA, DIMETHYLSILOXANE TREATED

For silica amorphous: Derived No Adverse Effects Level (NOAEL) in the range of 1000 mg/kg/d.

In humans, synthetic amorphous silica (SAS) is essentially non-toxic by mouth, skin or eyes, and by inhalation. Epidemiology studies show little evidence of adverse health effects due to SAS. Repeated exposure (without personal protection) may cause mechanical irritation of the eye and drying/cracking of the skin.

When experimental animals inhale synthetic amorphous silica (SAS) dust, it dissolves in the lung fluid and is rapidly eliminated. If swallowed, the vast majority of SAS is excreted in the faeces and there is little accumulation in the body.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	<b>~</b>	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	✓

**Legend:** X – Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

# **SECTION 12 Ecological information**

#### **Toxicity**

CRC Ceramic Armour Trigger	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
naphtha petroleum, heavy, hydrotreated	EC50	48h	Crustacea	>0.002mg/l	2
	EC50	96h	Algae or other aquatic plants	64mg/l	2
	EC50(ECx)	48h	Crustacea	>0.002mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
carnauba wax	Not Available	Not Available	Not Available	Not Available	Not Available
silica, dimethylsiloxane treated	Endpoint	Test Duration (hr)	Species	Value	Source

	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	4. US EPA, E		Registered Substances - Ecotoxicological Info ETOC Aquatic Hazard Assessment Data 6. I Data 8. Vendor Data	•	,

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. **DO NOT** discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

# **Bioaccumulative potential**

Ingredient	Bioaccumulation
carnauba wax	LOW (LogKOW = 3.46)
silica, dimethylsiloxane treated	LOW (LogKOW = -2.02)

# Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

# Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

# **Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

# **SECTION 14 Transport information**

# **Labels Required**

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
naphtha petroleum, heavy, hydrotreated	Not Available
carnauba wax	Not Available
silica, dimethylsiloxane treated	Not Available

#### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
naphtha petroleum, heavy, hydrotreated	Not Available
carnauba wax	Not Available
silica, dimethylsiloxane treated	Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002495	Additives Process Chemicals and Raw Materials Flammable Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

#### naphtha petroleum, heavy, hydrotreated is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule; Dangerous Goods 2005 - Schedule 2 Dangerous Goods in Limited Quantities and Consumer Commodities

New Zealand Workplace Exposure Standards (WES)

#### carnauba wax is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### silica, dimethylsiloxane treated is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

# **Additional Regulatory Information**

Not Applicable

# **Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

#### **Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

# Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
3.1C or 3.1D				10 L

# **Tracking Requirements**

Not Applicable

# **National Inventory Status**

National Inventory	ional Inventory Status					
Australia - AIIC / Australia Non-Industrial Use	Yes					
Canada - DSL	Yes					
Canada - NDSL	No (naphtha petroleum, heavy, hydrotreated; carnauba wax; silica, dimethylsiloxane treated)					
China - IECSC	Yes					
Europe - EINEC / ELINCS / NLP	No (silica, dimethylsiloxane treated)					
Japan - ENCS	No (carnauba wax)					
Korea - KECI	Yes					
New Zealand - NZIoC	Yes					
Philippines - PICCS	Yes					
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'					
Taiwan - TCSI	Yes					
Mexico - INSQ	Yes					
Vietnam - NCI	Yes					
Russia - FBEPH	No (silica, dimethylsiloxane treated)					
UAE - Control List (Banned/Restricted Substances)	No (naphtha petroleum, heavy, hydrotreated; carnauba wax; silica, dimethylsiloxane treated)					
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.					

# **SECTION 16 Other information**

Revision Date	16/10/2024
Initial Date	15/10/2024

# **SDS Version Summary**

Version	Date of Update	Sections Updated
2.1	15/10/2024	Composition / information on ingredients - Ingredients
3.1	16/10/2024	Toxicological information - Acute Health (inhaled), Hazards identification - Classification, Disposal considerations - Disposal, Exposure controls / personal protection - Engineering Control, Ecological Information - Environmental, Firefighting measures - Fire Fighter (extinguishing media), Firefighting measures - Fire Fighter (fire/explosion hazard), Firefighting measures - Fire Fighter (fire incompatibility), Handling and storage - Handling Procedure, Exposure controls / personal protection - Personal Protection (other), Accidental release measures - Spills (major), Accidental release measures - Spills (minor), Handling and storage - Storage (storage incompatibility), Handling and storage - Storage (storage requirement), Handling and storage - Storage (suitable container), Transport information - Transport, Transport Information

# Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

# **Definitions and abbreviations**

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ► STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ► TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

Disclaimer: This SDS was prepared by a third party for product identification purposes only and is not endorsed by or affiliated with the original brand owner.