



Safety Data Sheet

Page 1 of 11

LOCTITE 660

SDS No. : 164196

V001.2

Revision: 02.09.2018

printing date: 14.09.2022

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: LOCTITE 660

Intended use: Anaerobic Adhesive

Supplier:

Henkel New Zealand Ltd
2 Allens Rd
Auckland, 2013
New Zealand

Phone: +64 (9) 272-6710

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Not Classified as Dangerous Goods according to NZS 5433: 2012 and the Land Transport Rule: Dangerous Goods 2005.

HSNO Classification:

6.3A Class 6 - Toxicity, Subclass 6.3 - Skin irritant, Hazard Classification A

Class 6 - Toxicity, Subclass 6.5 - Sensitisation, Hazard Classification B

Class 6 - Toxicity, Subclass 6.4 - Eye irritant, Hazard Classification A

GHS Classification:

Hazard Class

Skin irritation

Serious eye irritation

Skin sensitizer

Target Organ Systemic Toxicant -

Single exposure

Hazard Category

Category 2

Category 2A

Category 1

Category 3

Target organ

respiratory tract irritation

Hazard pictogram:



Signal word:

Warning

Hazard statement(s):	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.
Precautionary Statement(s):	
Prevention:	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362 Take off contaminated clothing.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description: Mixture
Type of preparation: Anaerobic Sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Methacrylic acid, monoester with propane-1,2-diol	27813-02-1	30- < 60 %
Cumene hydroperoxide	80-15-9	< 3 %
Maleic acid	110-16-7	< 1 %
Methacrylic acid	79-41-4	< 1 %
Cumene	98-82-8	< 0.5 %
non hazardous ingredients~		30- < 80 %

SECTION 4 FIRST AID MEASURES

Ingestion:	Rinse mouth, do not induce vomiting, consult a doctor. Seek medical advice.
Skin:	Rinse with running water and soap. Seek medical advice.
Eyes:	Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash
Normal washroom facilities

Medical attention and special treatment: Treat symptomatically and supportively.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Foam, dry chemical or carbon dioxide.

Decomposition products in case of fire:: Oxides of carbon.
Oxides of sulfur.
Oxides of nitrogen.
Irritating organic vapours.

Particular danger in case of fire:: None

Special protective equipment for fire-fighters: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Avoid skin and eye contact.
See advice in section 8

Environmental precautions: Do not let product enter drains.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Use only in well-ventilated areas.
Avoid skin and eye contact.
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Conditions for safe storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Ceiling	STEL (ppm)	STEL (mg/m3)
METHACRYLIC ACID 79-41-4		20	70	-	-	-
CUMENE 98-82-8		-	-	-	75	375
CUMENE		25	125	-	-	-

Engineering controls:	Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.
Eye protection:	Wear protective glasses.
Skin protection:	Wear suitable protective clothing. Avoid skin-contact. Nitrile rubber gloves should be worn. Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.
Respiratory protection:	Use only in well-ventilated areas. If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	grey paste
Odor:	characteristic
Specific gravity:	1.1
Boiling point:	> 149 °C (> 300.2 °F)
Flash point: (Tagliabue closed cup)	> 93 °C (> 199.4 °F)
Vapor pressure: (; 26 °C (78.8 °F))	< 7 mbar
Density:	1.098 g/cm ³
Solubility in water:	Negligible
Viscosity (dynamic): (; Instrument: HBT; speed of rotation: 5 min ⁻¹ ; Spindle No: TB; Method: ;; LCT STM 10; Viscosity Brookfield)	150,000 - 350,000 mPa.s
VOC content: (2010/75/EC)	< 3.00 %

SECTION 10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions.
Incompatible materials:	Reacts with strong oxidants.
Hazardous decomposition products:	May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.
Hazardous polymerization:	None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.

SECTION 11 TOXICOLOGICAL INFORMATION**Health Effects:****Ingestion:**

May be harmful if swallowed.

Skin:

Causes skin irritation.

Eyes:

May cause allergic skin reaction.

Causes serious eye damage.

Inhalation:

May cause respiratory tract irritation.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	LD50	> 2,000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
	LD50	> 5,000 mg/kg	dermal		rabbit	not specified
Cumene hydroperoxide 80-15-9	LD50	550 mg/kg	oral		rat	not specified
	LD50	1,200 - 1,520 mg/kg	dermal			not specified
Maleic acid 110-16-7	LD50	708 mg/kg	oral		rat	not specified
	LD50	1,560 mg/kg			rabbit	not specified
Methacrylic acid 79-41-4	LD50	1,320 mg/kg	dermal		rat	OECD Guideline 401 (Acute Oral Toxicity)
	LC50	> 3.6 mg/l	oral	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
	LD50	500 - 1,000 mg/kg	inhalation		rabbit	Dermal Toxicity Screening
Cumene 98-82-8	LD50	2,700 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
	LC50	39 mg/l	inhalation	4 h	rat	not specified
	LD50	> 10,000 mg/kg	dermal		rabbit	not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	not irritating	24 h	rabbit	Draize Test
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
Maleic acid 110-16-7	irritating	24 h	human	Patch Test
Methacrylic acid 79-41-4	corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Cumene 98-82-8	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Maleic acid 110-16-7	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Methacrylic acid 79-41-4	corrosive		rabbit	Draize Test
Cumene 98-82-8	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Maleic acid 110-16-7	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Maleic acid 110-16-7	sensitising	Mouse local lymphnode assay (LLNA)	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Cumene 98-82-8	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay	with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	not specified
Maleic acid 110-16-7	negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay	no data with and without		Ames Test OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Methacrylic acid 79-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Methacrylic acid 79-41-4	negative	inhalation		mouse	OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
Cumene 98-82-8	negative negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without with and without with and without without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
Cumene 98-82-8	negative	inhalation: gas		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	NOAEL=300 mg/kg	oral: gavage		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified
Maleic acid 110-16-7	NOAEL=>= 40 mg/kg	oral: feed	90 ddaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Cumene 98-82-8	NOAEL=> 535.8 mg/kg	oral: feed	28 ddaily	rat	not specified
Cumene 98-82-8	NOAEL=125 ppm	inhalation: vapour	14 w6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

SECTION 12. ECOLOGICAL INFORMATION

General ecological information:

Do not empty into drains / surface water / ground water., May cause long-term adverse effects in the aquatic environment.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	LC50	493 mg/l	Fish	48 h	Leuciscus idus melanotus	DIN 38412-15
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	EC50	> 143 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	EC50	> 97.2 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	NOEC	> 97.2 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	EC10	1,140 mg/l	Bacteria	16 h		not specified
Cumene hydroperoxide 80-15-9	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min		not specified
Maleic acid 110-16-7	LC50	> 245 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
Maleic acid 110-16-7	EC50	42.81 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Maleic acid 110-16-7	EC50	74.35 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid 79-41-4	LC50	85 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OTS 797.1400 (Fish Acute Toxicity Test)
Methacrylic acid 79-41-4	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
Methacrylic acid 79-41-4	NOEC	8.2 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid 79-41-4	EC50	45 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid 79-41-4	EC10	100 mg/l	Bacteria	17 h		not specified
Cumene 98-82-8	LC50	4.8 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene 98-82-8	EC50	4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene	EC50	2.6 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline

Cumene 98-82-8	EC10	211 mg/l	Bacteria	24 h	(new name: Pseudokirchneriella subcapitata)	201 (Alga, Growth Inhibition Test) DIN 38412, part 8 (Pseudomonas Zellvermehrungshe mm-Test)
-------------------	------	----------	----------	------	---	---

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	readily biodegradable	aerobic	94.2 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Maleic acid 110-16-7	readily biodegradable	aerobic	97.08 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
Methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Cumene 98-82-8		aerobic	86 %	ISO 10708 (BODIS-Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	0.97				20 °C	not specified
Cumene hydroperoxide 80-15-9		9.1		calculation		OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Cumene hydroperoxide 80-15-9	2.16					not specified
Maleic acid 110-16-7	-1.3				20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Methacrylic acid 79-41-4	0.93				22 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Cumene 98-82-8		35.5		Carassius auratus		OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Cumene 98-82-8	3.55				23 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

SECTION 14. TRANSPORT INFORMATION

Dangerous Goods information:

Not Classified as Dangerous Goods according to NZS 5433: 2012 and the Land Transport Rule: Dangerous Goods 2005.

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

HSNO Approval Number: HSR002670

Site and Storage: Refer to the site and storage requirements for this Group Standard.
Refer to the HSNO controls for approved hazardous substances.

NZIoC: Compliant for NZIOC

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

- STEL - Short term exposure limit
- TWA - Time weighted average
- HSNO - Hazardous Substances and New Organisms
- GHS: Globally Harmonized System
- CAS: Chemical Abstracts Service
- LD 50: Lethal Dose 50%
- LC 50: Lethal Concentration 50%
- IMDG: International Maritime Dangerous Goods code
- IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

Reason for issue: Corrected information in Section(s): involved chapters: 15

Date of previous issue: 24.07.2017

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.