

CRC(NZ) Paint IT Aerosol

CRC Industries (CRC Industries New Zealand)

Chemwatch: **7941-39** Version No: **2.1**

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 4

Initial Date: 24/02/2025 Revision Date: 24/02/2025 Print Date: 28/10/2025 S.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

| Product name | CRC(NZ) Paint IT Aerosol |
|-------------------------------|--------------------------|
| Chemical Name | Not Applicable |
| Synonyms | Not Available |
| Proper shipping name | AEROSOLS |
| Chemical formula | Not Applicable |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified us | es |
|------------------------|----|
|------------------------|----|

Glossy coloured coating, Application is by spray atomisation from a hand held aerosol pack , Use according to manufacturer's directions.

Details of the manufacturer or importer of the safety data sheet

| Registered company name | CRC Industries (CRC Industries New Zealand) |
|-------------------------|---|
| Address | 10 Highbrook Drive East Tamaki Auckland New Zealand |
| Telephone | +64 9 272 2700 |
| Fax | +64 9 274 9696 |
| Website | www.crc.co.nz |
| Email | - No EMAL ID NEEDED for NZ - JACK |

Emergency telephone number

| Association / Organisation | CRC Industries (CRC Industries New Zealand) | CHEMWATCH EMERGENCY RESPONSE (24/7) |
|-------------------------------------|--|-------------------------------------|
| Emergency telephone number(s) | NZ Poisons Centre 0800 POISON (0800 764 766) | +64 800 700 112 (ID#: 7941-39) |
| Other emergency telephone number(s) | 111 (NZ Emergency Services) | +61 3 9573 3188 |

SECTION 2 Hazards identification

Classification of the substance or mixture

| Classification ^[1] | Aerosols, Hazard Category 1, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Reproductive Toxicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2 |
|---|--|
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |
| Determined by Chemwatch using GHS/HSNO criteria | 2.1.2A, 6.1D (oral), 6.3A, 6.4A, 6.8B, 6.9B |

Label elements

Hazard pictogram(s)







Signal word

Danger

Hazard statement(s)

| H222+H229 | Extremely flammable aerosol. Pressurized container: may burst if heated. |
|-----------|--|
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361 | Suspected of damaging fertility or the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

Precautionary statement(s) Prevention

| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
|------|--|
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P260 | Do not breathe mist/vapours/spray. |

Precautionary statement(s) Response

| P308+P313 | IF exposed or concerned: Get medical advice/ attention. |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337+P313 | If eye irritation persists: Get medical advice/attention. |
| P301+P312 | IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell. |

Precautionary statement(s) Storage

| P405 | Store locked up. |
|-----------|--|
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| mixtures | | |
|---------------|--|--|
| CAS No | %[weight] | Name |
| 67-64-1 | 20-30 | acetone |
| 108-88-3 | 20-30 | toluene |
| Not Available | 1-5 | colour |
| 22464-99-9 | <1 | zirconium 2-ethylhexanoate |
| 96-29-7 | <0.1 | methyl ethyl ketoxime |
| 68476-85-7. | 23-45 | hydrocarbon propellant |
| Legend: | Classified by Chemwatch; 2. Classification dr. 1272/2008 - Annex VI; 4. Classification drawn fr. | awn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No om C&L * EU IOELVs available |

SECTION 4 First aid measures

| Eye Contact | If aerosols come in contact with the eyes: Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
|--------------|---|
| Skin Contact | If solids or aerosol mists are deposited upon the skin: Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation. |
| Inhalation | If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. |
| Ingestion | If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. |

Indication of any immediate medical attention and special treatment needed

For petroleum distillates

- In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption decontamination (induced emesis or lavage) is controversial and should be considered on the merits of each individual case; of course the usual precautions of an endotracheal tube should be considered prior to lavage, to prevent aspiration.
- · Individuals intoxicated by petroleum distillates should be hospitalized immediately, with acute and continuing attention to neurologic and cardiopulmonary function.
- · Positive pressure ventilation may be necessary.
- · Acute central nervous system signs and symptoms may result from large ingestions of aspiration-induced hypoxia.
- · After the initial episode,individuals should be followed for changes in blood variables and the delayed appearance of pulmonary oedema and chemical pneumonitis. Such patients should be followed for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated.
- · Gastrointestinal symptoms are usually minor and pathological changes of the liver and kidneys are reported to be uncommon in acute intoxications.
- · Chlorinated and non-chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur. Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

Treat symptomatically.

For acute or short term repeated exposures to acetone:

- Symptoms of acetone exposure approximate ethanol intoxication.
- About 20% is expired by the lungs and the rest is metabolised. Alveolar air half-life is about 4 hours following two hour inhalation at levels near the Exposure Standard; in overdose, saturable metabolism and limited clearance, prolong the elimination half-life to 25-30 hours.
- There are no known antidotes and treatment should involve the usual methods of decontamination followed by supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Management:

Measurement of serum and urine acetone concentrations may be useful to monitor the severity of ingestion or inhalation.

Inhalation Management:

- ▶ Maintain a clear airway, give humidified oxygen and ventilate if necessary.
- If respiratory irritation occurs, assess respiratory function and, if necessary, perform chest X-rays to check for chemical pneumonitis.
- Consider the use of steroids to reduce the inflammatory response.
- ▶ Treat pulmonary oedema with PEEP or CPAP ventilation.

Dermal Management:

- P Remove any remaining contaminated clothing, place in double sealed, clear bags, label and store in secure area away from patients and staff.
- Irrigate with copious amounts of water.
- An emollient may be required.

Eye Management:

- Irrigate thoroughly with running water or saline for 15 minutes.
- Stain with fluorescein and refer to an ophthalmologist if there is any uptake of the stain.

Oral Management:

- No GASTRIC LAVAGE OR EMETIC
- ▶ Encourage oral fluids.

Systemic Management:

- Monitor blood glucose and arterial pH.
- Ventilate if respiratory depression occurs.
- If patient unconscious, monitor renal function.
- Symptomatic and supportive care.

The Chemical Incident Management Handbook:

Guy's and St. Thomas' Hospital Trust, 2000

BIOLOGICAL EXPOSURE INDEX

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant

Sampling Time

Index

Comments

Acetone in urine End of shift 50 mg/L NS

NS: Non-specific determinant; also observed after exposure to other material

Following acute or short term repeated exposures to toluene:

- Toluene is absorbed across the alveolar barrier, the blood/air mixture being 11.2/15.6 (at 37 degrees C.) The concentration of toluene, in expired breath, is of the order of 18 ppm following sustained exposure to 100 ppm. The tissue/blood proportion is 1/3 except in adipose where the proportion is 8/10.
- Metabolism by microsomal mono-oxygenation, results in the production of hippuric acid. This may be detected in the urine in amounts between 0.5 and 2.5 g/24 hr which represents, on average 0.8 gm/gm of creatinine. The biological half-life of hippuric acid is in the order of 1-2 hours.
- Primary threat to life from ingestion and/or inhalation is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (eg cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 <50 mm Hg or pCO2 > 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial damage has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenaline) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

DeterminantIndexSampling TimeCommentso-Cresol in urine0.5 mg/LEnd of shiftBHippuric acid in urine1.6 g/g creatinineEnd of shiftB, NS

NS: Non-specific determinant; also observed after exposure to other material

0.05 mg/L

B: Background levels occur in specimens collected from subjects NOT exposed

SECTION 5 Firefighting measures

Extinguishing media

Toluene in blood

- Alcohol stable foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

SMALL FIRE:

Water spray, dry chemical or CO2

LARGE FIRE:

Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility

 Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Prior to last shift of workweek

Advice for firefighters

| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. |
|-----------------------|--|
| Fire/Explosion Hazard | Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark. Combustion products include: carbon monoxide (CO) Combustible. Will burn if ignited. carbon dioxide (CO2) nitrogen oxides (NOx) metal oxides other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. |

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| | • . |
|--------------|---|
| Minor Spills | Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation. |
| Major Spills | Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

| Safe handling | Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. |
|-------------------|---|
| Other information | Store below 38 deg. C. Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can Store in original containers in approved flammable liquid storage area. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. No smoking, naked lights, heat or ignition sources. Keep containers securely sealed. |

Conditions for safe storage, including any incompatibilities

| Suitable container | Aerosol dispenser. Check that containers are clearly labelled. |
|-------------------------|---|
| Storage incompatibility | Avoid reaction with oxidising agents |

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|---|--------------------------------|---|--------------------------|--------------------------|---------------|---|
| New Zealand Workplace Exposure Standards (WES) | acetone | Acetone | 500 ppm / 1185 mg/m3 | 2375 mg/m3 / 1000 ppm | Not Available | bio - Exposure can also be estimated by biological monitoring |
| New Zealand Workplace Exposure Standards (WES) | toluene | Toluene (Toluol) | 20 ppm / 75 mg/m3 | 377 mg/m3 / 100 ppm | Not Available | skin - Skin absorption oto - Ototoxin bio - Exposure can also be estimated by biological monitoring |
| New Zealand Workplace Exposure Standards (WES) | zirconium 2- ethylhexanoate | Inhalable dust (not otherwise classified) | 10 mg/m3 | Not Available | Not Available | Not Available |
| New Zealand Workplace Exposure Standards (WES) | zirconium 2- ethylhexanoate | Zirconium and compounds, as Zr | 5 mg/m3 | 10 mg/m3 | Not Available | Not Available |
| New Zealand Workplace Exposure Standards (WES) | zirconium 2- ethylhexanoate | Respirable dust (not otherwise classified) | 3 mg/m3 | Not Available | Not Available | Not Available |
| New Zealand Workplace Exposure Standards (WES) | hydrocarbon propellant | LPG (Liquefied petroleum gas) | 1000 ppm / 1800 mg/m3 | Not Available | Not Available | Not Available |

| Ingredient | Original IDLH | Revised IDLH |
|----------------------------|---------------|---------------|
| acetone | 2,500 ppm | Not Available |
| toluene | 500 ppm | Not Available |
| zirconium 2-ethylhexanoate | 25 mg/m3 | Not Available |
| methyl ethyl ketoxime | Not Available | Not Available |
| hydrocarbon propellant | Not Available | Not Available |

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Individual protection measures, such as personal protective equipment









Eye and face protection

- Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
- Close fitting gas tight goggles

Skin protection

See Hand protection below

Hands/feet protection

- ▶ No special equipment needed when handling small quantities.
- OTHERWISE:
- For potentially moderate exposures:
 - Wear general protective gloves, eg. light weight rubber gloves.
 - For potentially heavy exposures:
 - ▶ Wear chemical protective gloves, eg. PVC. and safety footwear.

Body protection

See Other protection below

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Skin cleansing cream.
- Other protection Eyewash unit.
 - ▶ The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.
 - ▶ Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.

BRETHERICK: Handbook of Reactive Chemical Hazards.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

CRC(NZ) Paint IT Aerosol

| Material | CPI |
|------------------|-----|
| PE/EVAL/PE | A |
| TEFLON | В |
| BUTYL | С |
| BUTYL/NEOPRENE | С |
| CPE | С |
| HYPALON | С |
| NATURAL RUBBER | С |
| NATURAL+NEOPRENE | С |
| NEOPRENE | С |
| NEOPRENE/NATURAL | С |
| NITRILE | С |
| NITRILE+PVC | С |

Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|---------------------------------------|-------------------------|-------------------------|-----------------------------|
| up to 10 x ES | AX-AUS P2 | - | AX-PAPR-AUS / Class 1 P2 |
| up to 50 x ES | - | AX-AUS / Class 1 P2 | - |
| up to 100 x ES | - | AX-2 P2 | AX-PAPR-2 P2 ^ |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

| PVA | С |
|-------------------|---|
| PVC | С |
| PVDC/PE/PVDC | С |
| SARANEX-23 | С |
| SARANEX-23 2-PLY | С |
| VITON | С |
| VITON/CHLOROBUTYL | С |
| VITON/NEOPRENE | С |

- * CPI Chemwatch Performance Index
- A: Best Selection
- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection factor | Maximum gas/vapour concentration present in air p.p.m. (by volume) | Half-face Respirator | Full-Face Respirator |
|---|--|-------------------------|-------------------------|
| up to 10 | 1000 | AX-AUS / Class 1 | - |
| up to 50 | 1000 | - | AX-AUS / Class 1 |
| up to 50 | 5000 | Airline * | - |
| up to 100 | 5000 | - | AX-2 |
| up to 100 | 10000 | - | AX-3 |
| 100+ | | - | Airline** |

^{** -} Continuous-flow or positive pressure demand.

A(All classes) = Organic vapours, B AUS or B1 = Acid gases, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 deg C)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| Appearance | Coloured highly flammable liquid with strong solvent like odour; does not mix with water. | | | |
|--|---|---|----------------|--|
| | | | | |
| Physical state | Liquid | Relative density (Water = 1) | Not Available | |
| Odour | Not Available | Partition coefficient n- octanol / water | Not Available | |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available | |
| pH (as supplied) | Not Applicable | Decomposition temperature (°C) | Not Available | |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available | |
| Initial boiling point and boiling range (°C) | 56 | Molecular weight (g/mol) | Not Applicable | |
| Flash point (°C) | *-81 (propellant) | Taste | Not Available | |
| Evaporation rate | Not Available | Explosive properties | Not Available | |
| Flammability | HIGHLY FLAMMABLE. | Oxidising properties | Not Available | |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available | |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available | |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available | |
| Solubility in water | Immiscible | pH as a solution (1%) | Not Applicable | |

| Vapour density (Air = 1) | >1 | VOC g/L | Not Available |
|---|---------------|---|---------------|
| Heat of Combustion (kJ/g) | Not Available | Ignition Distance (cm) | Not Available |
| Flame Height (cm) | Not Available | Flame Duration (s) | Not Available |
| Enclosed Space Ignition Time Equivalent (s/m3) | Not Available | Enclosed Space Ignition Deflagration Density (g/m3) | Not Available |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|------------------------------------|--|
| Chemical stability | Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| a) Acute Toxicity | There is sufficient evidence to classify this material as acutely toxic. | | |
|---|--|--|--|
| b) Skin Irritation/Corrosion | There is sufficient evidence to classify this material as skin corrosive or irritating. | | |
| c) Serious Eye Damage/Irritation | There is sufficient evidence to classify this material as eye damaging or irritating | | |
| d) Respiratory or Skin sensitisation | Based on available data, the classification criteria are not met. | | |
| e) Mutagenicity | Based on available data, the classification criteria are not met. | | |
| f) Carcinogenicity | Based on available data, the classification criteria are not met. | | |
| g) Reproductivity | There is sufficient evidence to classify this material as toxic to reproductivity | | |
| h) STOT - Single Exposure | There is sufficient evidence to classify this material as toxic to specific organs through single exposure | | |
| i) STOT - Repeated Exposure | There is sufficient evidence to classify this material as toxic to specific organs through repeated exposure | | |
| j) Aspiration Hazard | Based on available data, the classification criteria are not met. | | |
| Inhaled | Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss reflexes, lack of co-ordination, and vertigo. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal. WARNING:Intentional misuse by concentrating/inhaling contents may be lethal. | | |
| Ingestion | Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments | | |
| Skin Contact | Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Spray mist may produce discomfort Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effer examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Rep exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. | | |
| Еуе | There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain. The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated. | | |
| Chronic | Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. | | |

This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.

Ample evidence exists that this material directly causes reduced fertility

Ample evidence exists that developmental disorders are directly caused by human exposure to the material.

Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.

Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.

Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.

Main route of exposure to the gas in the workplace is by inhalation.

Intentional abuse (glue sniffing) or occupational exposure to toluene can result in chronic habituation. Chronic abuse has caused inco-ordination, tremors of the extremeties (due to widespread cerebrum withering), headache, abnormal speech, temporary memory loss, convulsions, coma, drowsiness, reduced colour perception, blindness, nystagmus (rapid, involuntary eye movements), hearing loss leading to deafness and mild dementia.

Workers exposed to acetone for long periods showed inflammation of the airways, stomach and small bowel, attacks of giddiness and loss of strength. Exposure to acetone may enhance the liver toxicity of chlorinated solvents.

| CDC(NZ) Daint IT Assess | TOXICITY | IRRITATION |
|--------------------------|--|---|
| CRC(NZ) Paint IT Aerosol | Not Available | Not Available |
| | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: 20000 mg/kg ^[2] | Eye (Human): 186300ppm - Mild |
| | Inhalation (Mouse) LC50: 44 mg/L4h ^[2] | Eye (Human): 500ppm |
| | Oral (Rat) LD50: 5800 mg/kg ^[2] | Eye (Rodent - rabbit): 10uL - Mild |
| acetone | | Eye (Rodent - rabbit): 20mg - Severe |
| acetone | | Eye (Rodent - rabbit): 20mg/24H - Moderate |
| | | Eye: adverse effect observed (irritating) ^[1] |
| | | Skin (Rodent - rabbit): 395mg - Mild |
| | | Skin (Rodent - rabbit): 500mg/24H - Mild |
| | | Skin: no adverse effect observed (not irritating) ^[1] |
| | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: 12124 mg/kg ^[2] | Eye (Human): 300ppm |
| | Inhalation (Rat) LC50: >13350 ppm4h ^[2] | Eye (Rodent - rabbit): 0.1mL |
| | Oral (Rat) LD50: 636 mg/kg ^[2] | Eye (Rodent - rabbit): 0.1mL - Severe |
| | | Eye (Rodent - rabbit): 100mg/30S - Mild |
| | | Eye (Rodent - rabbit): 2mg/24H - Severe |
| toluene | | Eye (Rodent - rabbit): 870ug - Mild |
| toluene | | Eye: adverse effect observed (irritating) ^[1] |
| | | Skin (Mammal - pig): 250uL/24H - Mild |
| | | Skin (Rodent - rabbit): 20mg/24H - Moderate |
| | | Skin (Rodent - rabbit): 435mg - Mild |
| | | Skin (Rodent - rabbit): 500mg - Moderate |
| | | Skin: adverse effect observed (irritating) ^[1] |
| | | Skin: no adverse effect observed (not irritating) ^[1] |
| | TOXICITY | IRRITATION |
| zirconium 2- | dermal (rat) LD50: >870 mg/kg ^[1] | Eye: no adverse effect observed (not irritating) ^[1] |
| ethylhexanoate | Inhalation (Rat) LC50: >4.3 mg/l4h ^[1] | Skin (Rodent - guinea pig): 24% |
| | Oral (Rat) LD50: >=2000 mg/kg ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| methyl ethyl ketoxime | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: >184<1840 mg/kg ^[1] | Eye (Rodent - rabbit): 100uL - Severe |
| | Inhalation (Rat) LC50: >4.83 mg/l4h ^[1] | Eye: adverse effect observed (irreversible damage) ^[1] |

| | Oral (Rat) LD50: >900 mg/kg ^[1] | Skin: adverse | effect observed (irritating) ^[1] | |
|---|--|------------------------|---|--|
| | TOXICITY | IRRITATION | | |
| hydrocarbon propellant | Inhalation (Rat) LC50: 658 mg/l4h ^[2] | Eye: no adver | se effect observed (not irritating) ^[1] | |
| | | Skin: no adver | rse effect observed (not irritating) ^[1] | |
| Legend: | Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances | | | |
| | | | | |
| ACETONE | For acetone: The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitizer, but it removes fat from the skin, and it also irritates the eye. Animal testing shows acetone may cause anaemia. Studies in humans have shown that exposure to acetone at a level of 2375 mg/m3 does not negatively impact an individual's emotional regulation, behaviour, or learning ability. | | | |
| TOLUENE | For toluene: Acute toxicity: Humans exposed to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis (sleepiness) and death. When inhaled or swallowed, toluene can cause severe central nervous system depression, and in large doses has a narcotic effect. 60mL has caused death. Death of heart muscle fibres, liver swelling, congestion and bleeding of the lungs and kidney injury were all found on autopsy. Exposure to inhalation at a concentration of 600 parts per million for 8 hours resulted in the same and more serious symptoms including euphoria (a feeling of well-being), dilated pupils, convulsions and nausea. | | | |
| ZIRCONIUM 2- ETHYLHEXANOATE | For aliphatic fatty acids (and salts) Acute oral (gavage) toxicity: The acute oral LD50 values in rats for both were greater than >2000 mg/kg bw Clinical signs were generally associated with poor condition following administration of high doses (salivation, diarrhoea, staining, piloerection and lethargy). There were no adverse effects on body weight in any study In some studies, excess test substance and/or irritation in the gastrointestinal tract was observed at necropsy. Skin and eye irritation potential, with a few stated exceptions, is chain length dependent and decreases with increasing chain length According to several OECD test regimes the animal skin irritation studies indicate that the C6-10 aliphatic acids are severely irritating or corrosive, while the C12 aliphatic acid is irritating, and the C14-22 aliphatic acids generally are not irritating or mildly irritating. Human skin irritation studies using more realistic exposures (30-minute,1-hour or 24-hours) indicate that the aliphatic acids have sufficient, good or very good skin compatibility. Animal eye irritation studies indicate that among the aliphatic acids, the C8-12 aliphatic acids are irritating to the eye while the C14-22 aliphatic acids are not irritating. Eye irritation potential of the ammonium salts does not follow chain length dependence; the C18 ammonium salts are corrosive to the eyes. Dermal absorption: The in vitro penetration of C10, C12, C14, C16 and C18 fatty acids (as sodium salt solutions) through rat skin decreases with increasing chain length. At 86.73 ug C16/cm2 and 91.84 ug C18/cm2, about 0.23% and less than 0.1% of the C16 and C18 soap solutions is absorbed after 24 h exposure, respectively. Sensitisation: No sensitisation data were located. Repeat dose oral (gavage or diet) exposure to aliphatic acids did not result in systemic toxicity with NOAELs greater than the limit dose of 1000 mg/kg bw. | | | |
| METHYL ETHYL KETOXIME | Fatty acid salts of low acute toxicity. Their potential to irritate the skin and eyes is dependent on chain length. Mammalian lymphocyte mutagen *Huls Canada ** Merck The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. For methyl ethyl ketoxime (MEKO): At medium to high concentrations, MEKO increased the rate of liver tumours in animal testing. This seems to be due to the breakdown of MEKO into a cancer-causing substance, and occurred more often in males. MEKO does not seem to cause mutations. Repeated exposure appeared to cause effects on the nose, spleen, liver, kidney and blood. | | | |
| HYDROCARBON PROPELLANT | inhalation of the gas | | | |
| ACETONE & TOLUENE | The material may cause skin irritation after prolothe production of vesicles, scaling and thickenin | | may produce on contact skin redness, swelling, | |
| ZIRCONIUM 2- ETHYLHEXANOATE & HYDROCARBON PROPELLANT | No significant acute toxicological data identified | in literature search. | | |
| Acute Toxicity | ✓ | Carcinogenicity | x | |
| Skin Irritation/Corrosion | ✓ | Reproductivity | · | |
| Serious Eye Damage/Irritation | ~ | STOT - Single Exposure | ~ | |

| Respiratory or Skin sensitisation | × | STOT - Repeated Exposure | * |
|-----------------------------------|---|--------------------------|---|
| Mutagenicity | × | Aspiration Hazard | × |

Legend:

🗶 – Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

| | Endpoint | Test Duration (hr) | Species | Value | Source |
|--------------------------------|------------------|--------------------|-------------------------------|-----------------------|------------------|
| CRC(NZ) Paint IT Aerosol | Not Available | Not Available | Not Available | Not Available | Not Available |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| | EC50 | 72h | Algae or other aquatic plants | 5600- 10000mg/L | 4 |
| | EC50 | 48h | Crustacea | 6098.4mg/L | 5 |
| acetone | EC50 | 96h | Algae or other aquatic plants | 9.873- 27.684mg/l | 4 |
| | NOEC(ECx) | 12h | Fish | 0.001mg/L | 4 |
| | LC50 | 96h | Fish | 3744.6- 5000.7mg/L | 4 |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| | EC50 | 72h | Algae or other aquatic plants | 12.5mg/L | 4 |
| toluene | EC50 | 48h | Crustacea | 3.78mg/L | 5 |
| | NOEC(ECx) | 168h | Crustacea | 0.74mg/l | 2 |
| | EC50 | 96h | Algae or other aquatic plants | >376.71mg/L | 4 |
| | LC50 | 96h | Fish | 5-35mg/l | 4 |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| -! | NOEC(ECx) | 72h | Algae or other aquatic plants | 0.004mg/L | 2 |
| zirconium 2- ethylhexanoate | EC50 | 72h | Algae or other aquatic plants | >0.042mg/L | 2 |
| Ž | EC50 | 48h | Crustacea | >0.17mg/l | 2 |
| | LC50 | 96h | Fish | >100mg/l | 2 |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| | BCF | 1008h | Fish | 0.5-0.6 | 7 |
| methyl ethyl ketoxime | EC50 | 72h | Algae or other aquatic plants | ~6.09mg/l | 2 |
| memyr emyr ketoxime | EC50 | 48h | Crustacea | ~201mg/l | 2 |
| | NOEC(ECx) | 72h | Algae or other aquatic plants | ~1.02mg/l | 2 |
| | LC50 | 96h | Fish | >100mg/l | 2 |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| | EC50 | 96h | Algae or other aquatic plants | 7.71mg/l | 2 |
| hydrocarbon propollant | | 96h | Algae or other aquatic plants | 7.71mg/l | 2 |
| hydrocarbon propellant | EC50(ECx) | 9011 | | | |

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|------------|---------------------------|----------------------------------|
| acetone | LOW (Half-life = 14 days) | MEDIUM (Half-life = 116.25 days) |
| toluene | LOW (Half-life = 28 days) | LOW (Half-life = 4.33 days) |

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|-----------------------|-------------------------|------------------|
| methyl ethyl ketoxime | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|------------------------|---------------------|
| acetone | LOW (BCF = 0.69) |
| toluene | LOW (BCF = 90) |
| methyl ethyl ketoxime | LOW (BCF = 5.8) |
| hydrocarbon propellant | LOW (LogKOW = 3.39) |

Mobility in soil

| Ingredient | Mobility | |
|-----------------------|------------------------|--|
| acetone | HIGH (Log KOC = 1.981) | |
| toluene | LOW (Log KOC = 268) | |
| methyl ethyl ketoxime | LOW (Log KOC = 130.8) | |

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ▶ Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- ▶ **DO NOT** incinerate or puncture aerosol cans.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 Transport information

Labels Required

| | 2 |
|------------------|----------------|
| Marine Pollutant | NO |
| HAZCHEM | Not Applicable |

Land transport (UN)

| 14.1. UN number or ID number | 1950 | | |
|------------------------------------|----------------------------|-----------------------------|--|
| 14.2. UN proper shipping name | AEROSOLS | | |
| 14.3. Transport hazard class(es) | Class Subsidiary Hazard | 2.1 Not Applicable | |
| 14.4. Packing group | Not Applicable | | |
| 14.5. Environmental hazard | Not Applicable | | |
| 14.6. Special precautions for user | Special provisions | 63; 190; 277; 327; 344; 381 | |

| | Limited quantity | 1000ml |
|--|------------------|--------|
|--|------------------|--------|

Air transport (ICAO-IATA / DGR)

| 14.1. UN number | 1950 | | | | | |
|------------------------------------|---|-----------------------------|----------------|--|--|--|
| 14.2. UN proper shipping name | Aerosols, flammable | | | | | |
| | ICAO/IATA Class | 2.1 | | | | |
| 14.3. Transport hazard class(es) | ICAO / IATA Subsidiary Hazard | Not Applicable | | | | |
| olass(es) | ERG Code | 10L | | | | |
| 14.4. Packing group | Not Applicable | | | | | |
| 14.5. Environmental hazard | Not Applicable | | | | | |
| | Special provisions | | A145 A167 A802 | | | |
| 14.6. Special precautions for user | Cargo Only Packing Instructions | | 203 | | | |
| | Cargo Only Maximum Qty / Pack | | 150 kg | | | |
| | Passenger and Cargo Packing Instructions | | 203 | | | |
| | Passenger and Cargo Maximum Qty / Pack | | 75 kg | | | |
| | Passenger and Cargo Limited Quantity Packing Instructions | | Y203 | | | |
| | Passenger and Cargo Limited Qu | antity Packing Instructions | 1203 | | | |

Sea transport (IMDG-Code / GGVSee)

| 1950 | | | |
|--------------------|--|--|--|
| AEROSOLS | | | |
| IMDG Class | | 2.1 | |
| IMDG Subsidiary Ha | Hazard Not Applicable | | |
| Not Applicable | | | |
| Not Applicable | | | |
| EMS Number | F-D, | , S-U | |
| Special provisions | sions 63 190 277 327 344 381 959 | | |
| Limited Quantities | Limited Quantities 1000 ml | | |
| | AEROSOLS IMDG Class IMDG Subsidiary Ha Not Applicable Not Applicable EMS Number Special provisions | AEROSOLS IMDG Class IMDG Subsidiary Hazard Not Applicable Not Applicable EMS Number F-D Special provisions 63 1 | |

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|----------------------------|----------------|
| acetone | Not Applicable |
| toluene | Not Applicable |
| zirconium 2-ethylhexanoate | Not Applicable |
| methyl ethyl ketoxime | Not Applicable |
| hydrocarbon propellant | Not Applicable |

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|----------------------------|----------------|
| acetone | Not Applicable |
| toluene | Not Applicable |
| zirconium 2-ethylhexanoate | Not Applicable |
| methyl ethyl ketoxime | Not Applicable |
| hydrocarbon propellant | Not Applicable |

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

| HSR Number | Group Standard | | |
|------------|--|--|--|
| HSR002515 | Aerosols Flammable Group Standard 2020 | | |

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

acetone is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

toluene is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

zirconium 2-ethylhexanoate is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

methyl ethyl ketoxime is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

hydrocarbon propellant is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

Additional Regulatory Information

Not Applicable

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class | Quantity (Closed Containers) | Quantity (Open Containers) |
|--------------|------------------------------------|------------------------------------|
| 2.1.2A | 3 000 L (aggregate water capacity) | 3 000 L (aggregate water capacity) |

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Class of substance | Quantities |
|--------------------|----------------|
| Not Applicable | Not Applicable |

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class | Gas (aggregate water capacity in mL) | Liquid (L) | Solid (kg) | Maximum quantity per package for each classification |
|--------------|--------------------------------------|------------|------------|--|
| 2.1.2A | | | | 1L (aggregate water capacity) |

Tracking Requirements

Not Applicable

National Inventory Status

| National Inventory | Status | | | |
|---|---|--|--|--|
| Australia - AIIC / Australia Non-Industrial Use | Yes | | | |
| Canada - DSL | Yes | | | |
| Canada - NDSL | No (acetone; toluene; zirconium 2-ethylhexanoate; methyl ethyl ketoxime; hydrocarbon propellant) | | | |
| China - IECSC | Yes | | | |
| Europe - EINEC / ELINCS / NLP | Yes | | | |
| Japan - ENCS | Yes | | | |
| Korea - KECI | Yes | | | |
| New Zealand - NZIoC | Yes | | | |
| Philippines - PICCS | Yes | | | |
| USA - TSCA | All chemical substances in this product have been designated as TSCA Inventory 'Active' | | | |
| Taiwan - TCSI | Yes | | | |
| Mexico - INSQ | No (zirconium 2-ethylhexanoate) | | | |
| Vietnam - NCI | Yes | | | |
| Russia - FBEPH | Yes | | | |
| UAE - Control List (Banned/Restricted Substances) | No (acetone; toluene; zirconium 2-ethylhexanoate; methyl ethyl ketoxime; hydrocarbon propellant) | | | |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. | | | |

SECTION 16 Other information

| Revision Date | 24/02/2025 |
|---------------|------------|
| Initial Date | 24/02/2025 |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|-------------------|---|
| 2.1 | 24/02/2025 | Toxicological information - Acute Health (eye), Toxicological information - Acute Health (inhaled), Toxicological information - Acute Health (skin), Toxicological information - Acute Health (swallowed), Hazards identification - Classification, Ecological Information - Environmental, Exposure controls / personal protection - Exposure Standard, Firefighting measures - Fire Fighter (fire fighting), First Aid measures - First Aid (swallowed), Handling and storage - Handling Procedure, Exposure controls / personal protection - Personal Protection (Respirator), Accidental release measures - Spills (major), Handling and storage - Storage (storage incompatibility), Toxicological information - Toxicity and Irritation (Other), Identification of the substance / mixture and of the company / undertaking - Use, Name |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit

- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- ▶ IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- ► TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

Disclaimer: This SDS was prepared by a third party for product identification purposes only and is not endorsed by or affiliated with the original brand owner.