

CRC Food Grade Silicone (Aerosol) CRC Industries (CRC Industries New Zealand)

Chemwatch: **5611-17** Version No: **2.1**

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 3

Initial Date: 02/06/2023 Revision Date: 02/06/2023 Print Date: 21/08/2025 S.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	CRC Food Grade Silicone (Aerosol)
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Lubricant.
	Use according to manufacturer's directions.

Details of the manufacturer or importer of the safety data sheet

Registered company name	CRC Industries (CRC Industries New Zealand)
Address	10 Highbrook Drive East Tamaki Auckland New Zealand
Telephone	+64 9 272 2700
Fax	+64 9 274 9696
Website	www.crc.co.nz
Email	- No EMAL ID NEEDED for NZ - JACK

Emergency telephone number

Association / Organisation	CRC Industries (CRC Industries New Zealand)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	NZ Poisons Centre 0800 POISON (0800 764 766)	+64 800 700 112 (ID#: 5611-17)
Other emergency telephone number(s)	111 (NZ Emergency Services)	+61 3 9573 3188

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification ^[1]	Aerosols, Hazard Category 1, Skin Corrosion/Irritation Category 2, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Reproductive Toxicity Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 2	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Determined by Chemwatch using GHS/HSNO criteria	2.1.2A, 6.3A, 6.8B, 6.9B (narcotic effects), 9.1B	

Label elements

Hazard pictogram(s)









Signal word

Danger

Hazard statement(s)

H222+H229	Extremely flammable aerosol. Pressurized container: may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	
P391	P391 Collect spillage.	
P302+P352	IF ON SKIN: Wash with plenty of water and soap.	

Precautionary statement(s) Storage

P405	P405 Store locked up.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
--

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
92112-69-1	70	hexanes, mixture of isomers
63148-62-9	3	<u>polydimethylsiloxane</u>
68476-85-7.	27	hydrocarbon propellant
Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

SECTION 4 First aid measures

Description of first aid measures

If aerosols come in contact with the eyes:

Eye Contact

- ▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ► Transport to hospital or doctor without delay.
- ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact	If solids or aerosol mists are deposited upon the skin: Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation.		
Inhalation	If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.		
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay. 		

Indication of any immediate medical attention and special treatment needed

For petroleum distillates

- · In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption decontamination (induced emesis or lavage) is controversial and should be considered on the merits of each individual case; of course the usual precautions of an endotracheal tube should be considered prior to lavage, to prevent aspiration.
- · Individuals intoxicated by petroleum distillates should be hospitalized immediately, with acute and continuing attention to neurologic and cardiopulmonary function.
- · Positive pressure ventilation may be necessary.
- · Acute central nervous system signs and symptoms may result from large ingestions of aspiration-induced hypoxia.
- · After the initial episode,individuals should be followed for changes in blood variables and the delayed appearance of pulmonary oedema and chemical pneumonitis. Such patients should be followed for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated.
- · Gastrointestinal symptoms are usually minor and pathological changes of the liver and kidneys are reported to be uncommon in acute intoxications.
- · Chlorinated and non-chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur. Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

Treat symptomatically.

Following acute or short term repeated exposures to n-hexane:

- Large quantities of n-hexane are expired by the lungs after vapour exposure (50-60%). Humans exposed to 100 ppm demonstrate an n-hexane biological half life of 2 hours.
- Initial attention should be directed towards evaluation and support of respiration. Cardiac dysrhythmias are a potential complication.

INGESTION:

• Ipecac syrup should be considered for ingestion of pure hexane exceeding 2-3ml/kg. Extreme caution must be taken to avoid aspiration since small amounts of n-hexane intratracheally, produce a severe chemical pneumonitis.

[Ellenhorn and Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

BEIs represent the levels of determinants which are most likely to be observed in specimens collected in a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the Exposure Standard (ES or TLV).

Determinant Index Sampling Time Comments
1. 2,5-hexanedione in urine 5 mg/gm creatinine End of shift NS
2. n-Hexane in end-exhaled air SQ

NS: Non-specific determinant; Metabolite observed following exposure to other materials.

SQ: Semi-quantitative determinant; Interpretation may be ambiguous - should be used as a screening test or confirmatory test.

SECTION 5 Firefighting measures

Extinguishing media

SMALL FIRE:

▶ Water spray, dry chemical or CO2

LARGE FIRE:

Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	 Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark. Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) silicon dioxide (SiO2) other pyrolysis products typical of burning organic material. May emit clouds of acrid smoke

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

	5 · · · · · · · · · · · · · · · · · · ·
Minor Spills	Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation.
Major Spills	 Environmental hazard - contain spillage. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

	▶ DO NOT allow clothing wet with material to stay in contact with skin	
	▶ Avoid all personal contact, including inhalation.	
Safe handling	▶ Wear protective clothing when risk of exposure occurs.	
	▶ Use in a well-ventilated area.	
	▶ Prevent concentration in hollows and sumps.	
	▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of	
	can	
041	Store in original containers in approved flammable liquid storage area.	
Other information	▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped.	
	▶ No smoking, naked lights, heat or ignition sources.	
	► Keep containers securely sealed.	

Conditions for safe storage, including any incompatibilities

Suitable container	 ▶ Aerosol dispenser. ▶ Check that containers are clearly labelled.
Storage incompatibility	► Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	hydrocarbon propellant	LPG (Liquefied petroleum gas)	1000 ppm / 1800 mg/m3	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
hexanes, mixture of isomers	Not Available	Not Available
polydimethylsiloxane	Not Available	Not Available
hydrocarbon propellant	Not Available	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Individual protection measures, such as personal protective equipment











Eye and face protection

- Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
- ▶ No special equipment for minor exposure i.e. when handling small quantities.
- ▶ OTHERWISE: For potentially moderate or heavy exposures:
- Safety glasses with side shields.
- ▶ NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.
- Close fitting gas tight goggles

DO NOT wear contact lenses.

Skin protection

See Hand protection below

Hands/feet protection

- OTHERWISE:For potentially moderate exposures:
- Tor potentially moderate exposures.
- ▶ Wear general protective gloves, eg. light weight rubber gloves.

▶ No special equipment needed when handling small quantities.

- For potentially heavy exposures:
- Wear chemical protective gloves, eg. PVC. and safety footwear.

No special equipment needed when handling small quantities.

Body protection

See Other protection below

Other protection

- OTHERWISE:
 Overalls
- ► Skin cleansing cream.
- Eyewash unit.

Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	Air-line*	AX-2 P2	AX-PAPR-2 P2 ^
up to 10 x ES	-	AX-3 P2	-
10+ x ES	-	Air-line**	-

- * Continuous Flow; ** Continuous-flow or positive pressure demand
- ^ Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear highly flammable liquid with solvent like odour; does not mix with water		
Physical state	Liquid	Relative density (Water = 1)	0.68
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	<10	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Based on available data, the classification criteria are not met.
There is sufficient evidence to classify this material as skin corrosive or irritating.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
There is sufficient evidence to classify this material as toxic to reproductivity
There is sufficient evidence to classify this material as toxic to specific organs through single exposure
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. WARNING:Intentional misuse by concentrating/inhaling contents may be lethal.			
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments			
Skin Contact	This material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			
Eye	, , ,	nat the material may cause eye irritation in a substantial number of mation characterised by a temporary redness of the conjunctiva (similar to		
	occupational exposure. Constant or exposure over long periods to mixed hyd	s a suspicion this material directly reduces fertility. Scur and may cause some concern following repeated or long-term Irocarbons may produce stupor with dizziness, weakness and visual iver and kidney function. Skin exposure may result in drying and cracking		
Chronic	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous			
	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous Chronic inhalation or skin exposure to n-hexane may	e related hazards. system. They can occur as commercial products or as metabolic products.		
CRC Food Grade Silicone (Aerosol)	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous chronic inhalation or skin exposure to n-hexane may sensation.	e related hazards. system. They can occur as commercial products or as metabolic products, cause damage to nerve ends in extremities, e.g. finger, toes with loss of		
CRC Food Grade Silicone (Aerosol)	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous chronic inhalation or skin exposure to n-hexane may sensation.	e related hazards. system. They can occur as commercial products or as metabolic products. cause damage to nerve ends in extremities, e.g. finger, toes with loss of		
CRC Food Grade Silicone	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous chronic inhalation or skin exposure to n-hexane may sensation. TOXICITY Not Available	e related hazards. system. They can occur as commercial products or as metabolic products. cause damage to nerve ends in extremities, e.g. finger, toes with loss of IRRITATION Not Available		
CRC Food Grade Silicone (Aerosol) hexanes, mixture of	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous chronic inhalation or skin exposure to n-hexane may sensation. TOXICITY Not Available TOXICITY	e related hazards. system. They can occur as commercial products or as metabolic products, cause damage to nerve ends in extremities, e.g. finger, toes with loss of IRRITATION Not Available IRRITATION		
CRC Food Grade Silicone (Aerosol) hexanes, mixture of	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous: Chronic inhalation or skin exposure to n-hexane may sensation. TOXICITY Not Available TOXICITY Oral (Rat) LD50: >16507.5 mg/kg ^[1]	e related hazards. system. They can occur as commercial products or as metabolic products. cause damage to nerve ends in extremities, e.g. finger, toes with loss of IRRITATION Not Available IRRITATION Not Available		
CRC Food Grade Silicone (Aerosol) hexanes, mixture of	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous chronic inhalation or skin exposure to n-hexane may sensation. TOXICITY Not Available TOXICITY Oral (Rat) LD50: >16507.5 mg/kg[1] TOXICITY	e related hazards. system. They can occur as commercial products or as metabolic products, cause damage to nerve ends in extremities, e.g. finger, toes with loss of IRRITATION Not Available IRRITATION Not Available IRRITATION		
CRC Food Grade Silicone (Aerosol) hexanes, mixture of isomers	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous chronic inhalation or skin exposure to n-hexane may sensation. TOXICITY Not Available TOXICITY Oral (Rat) LD50: >16507.5 mg/kg ^[1] TOXICITY Dermal (rabbit) LD50: >3000 mg/kg ^[2]	e related hazards. system. They can occur as commercial products or as metabolic products, cause damage to nerve ends in extremities, e.g. finger, toes with loss of IRRITATION Not Available IRRITATION Not Available IRRITATION Eye (Rodent - rabbit): 100mg/1H - Mild		
CRC Food Grade Silicone (Aerosol) hexanes, mixture of isomers	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous chronic inhalation or skin exposure to n-hexane may sensation. TOXICITY Not Available TOXICITY Oral (Rat) LD50: >16507.5 mg/kg ^[1] TOXICITY Dermal (rabbit) LD50: >3000 mg/kg ^[2]	e related hazards. system. They can occur as commercial products or as metabolic products, cause damage to nerve ends in extremities, e.g. finger, toes with loss of IRRITATION Not Available IRRITATION Not Available IRRITATION Eye (Rodent - rabbit): 100mg/1H - Mild Eye (Rodent - rabbit): 100uL/24H - Mild		
CRC Food Grade Silicone (Aerosol) hexanes, mixture of isomers	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous chronic inhalation or skin exposure to n-hexane may sensation. TOXICITY Not Available TOXICITY Oral (Rat) LD50: >16507.5 mg/kg ^[1] TOXICITY Dermal (rabbit) LD50: >3000 mg/kg ^[2]	e related hazards. system. They can occur as commercial products or as metabolic products, cause damage to nerve ends in extremities, e.g. finger, toes with loss of IRRITATION Not Available IRRITATION Not Available IRRITATION Eye (Rodent - rabbit): 100mg/1H - Mild Eye (Rodent - rabbit): 100uL/24H - Mild Eye (Rodent - rabbit): 100uL/24H - Moderate		
CRC Food Grade Silicone (Aerosol) hexanes, mixture of isomers	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous chronic inhalation or skin exposure to n-hexane may sensation. TOXICITY Not Available TOXICITY Oral (Rat) LD50: >16507.5 mg/kg[1] TOXICITY Dermal (rabbit) LD50: >3000 mg/kg[2] Oral (Rat) LD50: >35000 mg/kg[2]	e related hazards. system. They can occur as commercial products or as metabolic products, cause damage to nerve ends in extremities, e.g. finger, toes with loss of IRRITATION Not Available IRRITATION Not Available IRRITATION Eye (Rodent - rabbit): 100mg/1H - Mild Eye (Rodent - rabbit): 100uL/24H - Mild Eye (Rodent - rabbit): 100uL/24H - Moderate Skin (Rodent - rabbit): 500uL/24H - Mild		
CRC Food Grade Silicone (Aerosol) hexanes, mixture of isomers	and redness of the skin. WARNING: Aerosol containers may present pressure gamma-diketones are generally toxic to the nervous chronic inhalation or skin exposure to n-hexane may sensation. TOXICITY Not Available TOXICITY Oral (Rat) LD50: >16507.5 mg/kg ^[1] TOXICITY Dermal (rabbit) LD50: >3000 mg/kg ^[2] Oral (Rat) LD50: >35000 mg/kg ^[2]	e related hazards. system. They can occur as commercial products or as metabolic products, cause damage to nerve ends in extremities, e.g. finger, toes with loss of IRRITATION Not Available IRRITATION Not Available IRRITATION Eye (Rodent - rabbit): 100mg/1H - Mild Eye (Rodent - rabbit): 100uL/24H - Mild Eye (Rodent - rabbit): 100uL/24H - Moderate Skin (Rodent - rabbit): 500uL/24H - Mild IRRITATION		

POLYDIMETHYLSILOXANE	No toxic response noted during 90 day subchronic inhalation toxicity studies The no observable effect level is 450 mg/m3. Non-irritating and non-sensitising in human patch test. [Xerox]* Siloxanes may impair liver and hormonal function, as well as the lung and kidney. They have not been found to be irritating to the skin and eyes. They may potentially cause cancer (tumours of the womb in females) and may cause impaired fertility or infertility. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.		
HYDROCARBON PROPELLANT	inhalation of the gas		
HEXANES, MIXTURE OF ISOMERS & HYDROCARBON PROPELLANT	No significant acute toxicological data identified in literature search.		
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	*	Reproductivity	*

STOT - Single Exposure

Serious Eye

Damage/Irritation

×

Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

🗶 – Data either not available or does not fill the criteria for classification Legend:

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
CRC Food Grade Silicone (Aerosol)	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
hexanes, mixture of isomers	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
polydimethylsiloxane	Not Available	Not Available	Not Available	Not Available	Not Availabl
	Endpoint	Test Duration (hr)	Species	Value	Source
h. d	EC50	96h	Algae or other aquatic plants	7.71mg/l	2
hydrocarbon propellant	EC50(ECx)	96h	Algae or other aquatic plants	7.71mg/l	2
	LC50	96h	Fish	24.11mg/l	2
Legend:	4. US EPA, Ec	·	ECHA Registered Substances - Ecotoxicologic ata 5. ECETOC Aquatic Hazard Assessment Da entration Data 8. Vendor Data	•	

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
hydrocarbon propellant	LOW (LogKOW = 3.39)

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

▶ DO NOT allow wash water from cleaning or process equipment to enter drains. • It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Product / Packaging Where in doubt contact the responsible authority. disposal ▶ Consult State Land Waste Management Authority for disposal. ▶ Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. ▶ DO NOT incinerate or puncture aerosol cans.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 Transport information

Labels Required



Marine Pollutant



HAZCHEM

Not Applicable

Land transport (UN)

14.1. UN number or ID number	1950		
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	
14.3. Transport hazard class(es)	Class Subsidiary Hazard	2.1 Not Applicable	
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Environmentally hazardous		
14.6. Special precautions for user	Special provisions 63; 190; 277; 327; 344; 381 Limited quantity 1000ml		

Air transport (ICAO-IATA / DGR)

14.1. UN number	1950			
14.2. UN proper shipping name	Aerosols, flammable (engine starting fluid)			
	ICAO/IATA Class 2.1			
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable		
01000(00)	ERG Code	10L		
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Environmentally hazardous			
	Special provisions		A1 A145 A167 A802	
	Cargo Only Packing Instructions		203	
	Cargo Only Maximum Qty / Pack		150 kg	
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		Forbidden	
ioi usei	Passenger and Cargo Maximum Qty / Pack		Forbidden	
	Passenger and Cargo Limited Quantity Packing Instructions		Forbidden	
	Passenger and Cargo Limited Maximum Qty / Pack			

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1950	
14.2. UN proper shipping name	AEROSOLS	
	IMDG Class	2.1

14.3. Transport hazard class(es)	IMDG Subsidiary Ha	azard Not Applicable		
14.4. Packing group	Not Applicable	Not Applicable		
14.5 Environmental hazard	Marine Pollutant			
14.6. Special precautions for user	EMS Number Special provisions Limited Quantities	F-D , S-U 63 190 277 327 344 381 959 1000 mJ		

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
hexanes, mixture of isomers	Not Available
polydimethylsiloxane	Not Available
hydrocarbon propellant	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
hexanes, mixture of isomers	Not Available
polydimethylsiloxane	Not Available
hydrocarbon propellant	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002515	Aerosols Flammable Group Standard 2020
HSR002552	Cosmetic Products Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

hexanes, mixture of isomers is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

polydimethylsiloxane is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

hydrocarbon propellant is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

Additional Regulatory Information

Not Applicable

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
2.1.2A	3 000 L (aggregate water capacity)	3 000 L (aggregate water capacity)

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
2.1.2A				1L (aggregate water capacity)

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	No (hexanes, mixture of isomers)	
Canada - NDSL	No (hexanes, mixture of isomers; polydimethylsiloxane; hydrocarbon propellant)	
China - IECSC	No (hexanes, mixture of isomers)	
Europe - EINEC / ELINCS / NLP	No (polydimethylsiloxane)	
Japan - ENCS	Yes	
Korea - KECI	No (hexanes, mixture of isomers)	
New Zealand - NZIoC	Yes	
Philippines - PICCS	No (hexanes, mixture of isomers)	
USA - TSCA	TSCA Inventory 'Active' substance(s) (polydimethylsiloxane; hydrocarbon propellant); No (hexanes, mixture of isomers)	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (hexanes, mixture of isomers)	
Vietnam - NCI	Yes	
Russia - FBEPH	No (hexanes, mixture of isomers)	
UAE - Control List (Banned/Restricted Substances)	No (hexanes, mixture of isomers; polydimethylsiloxane; hydrocarbon propellant)	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	02/06/2023
Initial Date	02/06/2023

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations

- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ► NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- ► IMSBC: International Maritime Solid Bulk Cargoes Code
- ▶ IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ► NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- ► TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

Disclaimer: This SDS was prepared by a third party for product identification purposes only and is not endorsed by or affiliated with the original brand owner.