

# **Coloured Zinc (Aerosol)**

# **CRC Industries (CRC Industries New Zealand)**

Chemwatch: **7924-71** Version No: **2.1** 

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 4

Initial Date: 03/02/2025 Revision Date: 03/02/2025 Print Date: 08/10/2025 S.GHS.NZL.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	Coloured Zinc (Aerosol)
Chemical Name	Not Applicable
Synonyms	2090 WHITE ZINC; 2096 GREEN ZINC; 2097 BLUE ZINC; 2098 YELLOW ZINC; 2100 RED ZINC; 2101 ORANGE ZINC; 2089, 2129 BACK ZINC; 1753473 BACK ZINC MAX
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Anticorrosive paint. Application is by spray atomisation from a handheld aerosol pack Application is by spray atomisation from a hand held aerosol pack Use according to manufacturer's directions.
--------------------------	---

# Details of the manufacturer or importer of the safety data sheet

Registered company name	CRC Industries (CRC Industries New Zealand)	
Address	Highbrook Drive East Tamaki Auckland New Zealand	
Telephone	+64 9 272 2700	
Fax	+64 9 274 9696	
Website	www.crc.co.nz	
Email	- No EMAL ID NEEDED for NZ - JACK	

#### **Emergency telephone number**

Association / Organisation	CRC Industries (CRC Industries New Zealand)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	NZ Poisons Centre 0800 POISON (0800 764 766)	+64 800 700 112 (ID#: 7924-71)
Other emergency telephone number(s)	111 (NZ Emergency Services)	+61 3 9573 3188

#### **SECTION 2 Hazards identification**

# Classification of the substance or mixture

Classification <sup>[1]</sup>	Aerosols, Hazard Category 1, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 2	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Determined by Chemwatch using GHS/HSNO criteria	2.1.2A, 6.1D (oral), 6.3A, 6.4A, 6.9B, 9.1B	

#### Hazard pictogram(s)









Signal word

Danger

# Hazard statement(s)

H222+H229	H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	

# Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	P211 Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe mist/vapours/spray.	

# Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P314	Get medical advice/attention if you feel unwell.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P391	91 Collect spillage.	

# Precautionary statement(s) Storage

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
--

# Precautionary statement(s) Disposal

**P501** Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

No further product hazard information.

# **SECTION 3 Composition / information on ingredients**

### Substances

See section below for composition of Mixtures

### Mixtures

CAS No	%[weight]	Name
68476-85-7.	25-35	LPG (liquefied petroleum gas)
108-88-3	10-30	toluene
67-64-1	10-25	acetone
7779-90-0	1-10	zinc phosphate
763-69-9	1-10	ethyl-3-ethoxypropionate
Legend:	Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

# **SECTION 4 First aid measures**

### **Description of first aid measures**

**Eye Contact** 

If aerosols come in contact with the eyes:

- ▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Transport to hospital or doctor without delay.

	▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.	
Skin Contact	If solids or aerosol mists are deposited upon the skin:  Flush skin and hair with running water (and soap if available).  Remove any adhering solids with industrial skin cleansing cream.  DO NOT use solvents.  Seek medical attention in the event of irritation.	
Inhalation	If aerosols, fumes or combustion products are inhaled:  Remove to fresh air.  Lay patient down. Keep warm and rested.  Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.  If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.  Transport to hospital, or doctor.	
Ingestion	<ul> <li>Avoid giving milk or oils.</li> <li>Not considered a normal route of entry.</li> <li>If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>	

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 Firefighting measures**

# **Extinguishing media**

SMALL FIRE:

Water spray, dry chemical or CO2

LARGE FIRE:

Water spray or fog.

# Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may
result

# Advice for firefighters

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> </ul>
Fire/Explosion Hazard	Combustion products include: carbon dioxide (CO2)  Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark. metal oxides other pyrolysis products typical of burning organic material. carbon monoxide (CO) Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. WARNING: Long standing in contact with air and light may result in the formation of potentially explosive peroxides.

# **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

# **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Wear protective clothing, impervious gloves and safety glasses.</li> <li>Shut off all possible sources of ignition and increase ventilation.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Clear area of all unprotected personnel and move upwind.</li> <li>Alert Emergency Authority and advise them of the location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear full body clothing with breathing apparatus.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

# Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>
Other information	<ul> <li>Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can</li> <li>Store in original containers in approved flammable liquid storage area.</li> <li>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</li> <li>No smoking, naked lights, heat or ignition sources.</li> <li>Keep containers securely sealed.</li> </ul>

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Aerosol dispenser.</li> <li>Check that containers are clearly labelled.</li> </ul>
Storage incompatibility	Avoid reaction with oxidising agents

# **SECTION 8 Exposure controls / personal protection**

# **Control parameters**

# Occupational Exposure Limits (OEL)

# INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	LPG (liquefied petroleum gas)	LPG (Liquefied petroleum gas)	1000 ppm / 1800 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	toluene	Toluene (Toluol)	20 ppm / 75 mg/m3	377 mg/m3 / 100 ppm	Not Available	skin - Skin absorption oto - Ototoxin bio - Exposure can also be estimated by biological monitoring
New Zealand Workplace Exposure Standards (WES)	acetone	Acetone	500 ppm / 1185 mg/m3	2375 mg/m3 / 1000 ppm	Not Available	bio - Exposure can also be estimated by biological monitoring
New Zealand Workplace Exposure Standards (WES)	zinc phosphate	Respirable dust (not otherwise classified)	3 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	zinc phosphate	Inhalable dust (not otherwise classified)	10 mg/m3	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
LPG (liquefied petroleum gas)	Not Available	Not Available
toluene	500 ppm	Not Available
acetone	2,500 ppm	Not Available
zinc phosphate	Not Available	Not Available
ethyl-3-ethoxypropionate	Not Available	Not Available

#### **Exposure controls**

#### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

#### Individual protection measures, such as personal protective equipment









# Close fitting gas tight goggles

#### **DO NOT** wear contact lenses

# Eye and face protection

 Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.

- ▶ No special equipment for minor exposure i.e. when handling small quantities.
- ▶ OTHERWISE: For potentially moderate or heavy exposures:
- Safety glasses with side shields.
- ▶ NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

#### Skin protection

# See Hand protection below

OTHERWISE

# Hands/feet protection

- ▶ No special equipment needed when handling small quantities.
- For potentially moderate exposures:
- Wear general protective gloves, eg. light weight rubber gloves.
- ▶ For potentially heavy exposures:
- ▶ Wear chemical protective gloves, eg. PVC. and safety footwear.

#### **Body protection**

See Other protection below

# No special equipment needed when handling small quantities.

- OTHERWISE: Overalls.
- Skin cleansing cream.
- Other protection
- Evewash unit.
  - The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.
  - Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.

BRETHERICK: Handbook of Reactive Chemical Hazards.

## Recommended material(s)

# **GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

#### "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection:

Coloured Zinc (Aerosol)

Material	CPI
PE/EVAL/PE	A
TEFLON	В
BUTYL	С
BUTYL/NEOPRENE	С
CPE	С
HYPALON	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
NITRILE+PVC	С
PVA	С
PVC	С
PVDC/PE/PVDC	С

### Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS P3	-	AX-PAPR-AUS / Class 1 P3
up to 50 x ES	-	AX-AUS / Class 1 P3	-
up to 100 x ES	-	AX-2 P3	AX-PAPR-2 P3 ^

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SARANEX-23	С
SARANEX-23 2-PLY	С
VITON	С
VITON/CHLOROBUTYL	С
VITON/NEOPRENE	С

<sup>\*</sup> CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

 $\label{eq:NOTE: As a series of factors will influence the actual performance of the glove,} \\$ 

a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

# **SECTION 9 Physical and chemical properties**

# Information on basic physical and chemical properties

Appearance	Coloured liquid aerosol with mild odour; does not mix with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	-81 (propellant)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Elevated temperatures.</li> <li>Presence of open flame.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# Information on toxicological effects

intermetion on textoologic	
a) Acute Toxicity	There is sufficient evidence to classify this material as acutely toxic.
b) Skin Irritation/Corrosion	There is sufficient evidence to classify this material as skin corrosive or irritating.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	There is sufficient evidence to classify this material as toxic to specific organs through repeated exposure
j) Aspiration Hazard	Based on available data, the classification criteria are not met.
Inhaled	There is strong evidence to suggest that this material can cause, if inhaled once, very serious, irreversible damage of organs. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.  Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.  Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.  Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.  The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Heart stoppage may result from cardiovascular collapse.  WARNING:Intentional misuse by concentrating/inhaling contents may be lethal.  Exposure to hydrocarbons may result in irregularity of heart beat. Symptoms of moderate poisoning may include dizziness, headache, nausea.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.  There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. At sufficiently high doses the material may be hepatotoxic (i.e. poisonous to the liver).  Not normally a hazard due to physical form of product.  Considered an unlikely route of entry in commercial/industrial environments  Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)
Skin Contact	There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs.  Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.  Spray mist may produce discomfort  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.  Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.  The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.
Еуе	Not considered to be a risk because of the extreme volatility of the gas.  There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.  The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated.  The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration
Chronic	Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.  Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.  This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.  Ample evidence exists that this material directly causes reduced fertility  Ample evidence exists that developmental disorders are directly caused by human exposure to the material.  Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.  Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.

Coloured Zinc (Aerosol)

TOXICITY

IRRITATION

	Not Available	Not Available	
LPG (liquefied petroleum	тохісіту	IRRITATION	
gas)	Inhalation (Rat) LC50: 658 mg/l4h <sup>[2]</sup>	Not Available	
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: 12124 mg/kg <sup>[2]</sup>	Eye (Human): 300ppm	
	Inhalation (Rat) LC50: >13350 ppm4h <sup>[2]</sup>	Eye (Rodent - rabbit): 0.1mL	
	Oral (Rat) LD50: 636 mg/kg <sup>[2]</sup>	Eye (Rodent - rabbit): 0.1mL - Severe	
		Eye (Rodent - rabbit): 100mg/30S - Mild	
		Eye (Rodent - rabbit): 2mg/24H - Severe	
		Eye (Rodent - rabbit): 870ug - Mild	
toluene		Eye: adverse effect observed (irritating) <sup>[1]</sup>	
		Skin (Mammal - pig): 250uL/24H - Mild	
		Skin (Rodent - rabbit): 20mg/24H - Moderate	
		Skin (Rodent - rabbit): 435mg - Mild	
		Skin (Rodent - rabbit): 500mg - Moderate	
		Skin: adverse effect observed (irritating) <sup>[1]</sup>	
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: 20000 mg/kg <sup>[2]</sup>	Eye (Human): 186300ppm - Mild	
	Inhalation (Mouse) LC50: 44 mg/L4h <sup>[2]</sup>	Eye (Human): 500ppm	
	Oral (Rat) LD50: 5800 mg/kg <sup>[2]</sup>	Eye (Rodent - rabbit): 10uL - Mild	
		Eye (Rodent - rabbit): 20mg - Severe	
acetone		Eye (Rodent - rabbit): 20mg/24H - Moderate	
		Eye: adverse effect observed (irritating) <sup>[1]</sup>	
		Skin (Rodent - rabbit): 395mg - Mild	
		Skin (Rodent - rabbit): 500mg/24H - Mild	
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	TOXICITY	IRRITATION	
zinc phosphate	Inhalation (Rat) LC50: >5.7 mg/L4h <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
	Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: 4076 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
ethyl-3-ethoxypropionate	Inhalation (Rat) LC50: 1250 ppm4h <sup>[2]</sup>	Skin (Rodent - rabbit): 500mg/24H - Mild	
	Oral (Rat) LD50: ~3200-5000 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.		
	Unless otherwise specified data extracted from RTEC	S - Register of Toxic Effect of chemical Substances	
LPG (LIQUEFIED	No significant acute toxicological data identified in liter	rature search.	
PETROLEUM GAS)	inhalation of the gas		
	For toluene: Acute toxicity: Humans exposed to high levels of toluene for short periods of time experience adverse central nervous sy effects ranging from headaches to intoxication, convulsions, narcosis (sleepiness) and death. When inhaled or swallowe		

PETROLEUM GAS)	No significant acute toxicological data identified in literature search. inhalation of the gas
TOLUENE	For toluene: Acute toxicity: Humans exposed to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis (sleepiness) and death. When inhaled or swallowed, toluene can cause severe central nervous system depression, and in large doses has a narcotic effect. 60mL has caused death. Death of heart muscle fibres, liver swelling, congestion and bleeding of the lungs and kidney injury were all found on autopsy. Exposure to inhalation at a concentration of 600 parts per million for 8 hours resulted in the same and more serious symptoms including euphoria (a feeling of well-being), dilated pupils, convulsions and nausea.
ACETONE	For acetone:  The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitizer, but it removes fat from the skin, and it also irritates the eye. Animal testing shows acetone may cause anaemia. Studies in humans have shown that exposure to acetone at a level of 2375 mg/m3 does not negatively impact an individual's emotional regulation, behaviour, or learning ability.

ETHYL-3- ETHOXYPROPIONATE	* Union Carbide ** Endura Manufacturing		
TOLUENE & ACETONE & ETHYL-3- ETHOXYPROPIONATE	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
Acute Toxicity	✓	Carcinogenicity	×
Skin Irritation/Corrosion	<b>~</b>	Reproductivity	×
Serious Eye Damage/Irritation	<b>✓</b>	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	<b>✓</b>
Mutagenicity	×	Aspiration Hazard	×

**Legend: X** − Data either not available or does not fill the criteria for classification

# **SECTION 12 Ecological information**

# **Toxicity**

	Endpoint	Test Duration (hr)	Species	Value	Source
Coloured Zinc (Aerosol)	Not Available	Not Available	Not Available	Not Available	Not Available
LDC (limusfied metaplessa	Endpoint	Test Duration (hr)	Species	Value	Source
LPG (liquefied petroleum gas)	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	12.5mg/L	4
	EC50	48h	Crustacea	3.78mg/L	5
toluene	NOEC(ECx)	168h	Crustacea	0.74mg/l	2
	EC50	96h	Algae or other aquatic plants	>376.71mg/L	4
	LC50	96h	Fish	5-35mg/l	4
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	EC50	72h	Algae or other aquatic plants	5600- 10000mg/L	4
	EC50	48h	Crustacea	6098.4mg/L	5
acetone	EC50	96h	Algae or other aquatic plants	9.873- 27.684mg/l	4
	NOEC(ECx)	12h	Fish	0.001mg/L	4
	LC50	96h	Fish	3744.6- 5000.7mg/L	4
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	EC50	72h	Algae or other aquatic plants	0.051mg/L	2
	EC50	48h	Crustacea	0.105mg/L	2
zinc phosphate	EC50	96h	Algae or other aquatic plants	0.042mg/L	2
	EC10(ECx)	168h	Algae or other aquatic plants	0.003mg/L	2
	LC50	96h	Fish	0.09mg/L	4
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	EC50	72h	Algae or other aquatic plants	>114.86mg/l	2
ethyl-3-ethoxypropionate	EC50	48h	Crustacea	970mg/l	1
	EC50(ECx)	48h	Crustacea	970mg/l	1
	LC50	96h	Fish	45.3mg/l	2
Legend:	4. US EPA, Ec		e ECHA Registered Substances - Ecotoxicologi Data 5. ECETOC Aquatic Hazard Assessment Di Centration Data 8. Vendor Data	•	

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
toluene	LOW (Half-life = 28 days)	LOW (Half-life = 4.33 days)
acetone	LOW (Half-life = 14 days)	MEDIUM (Half-life = 116.25 days)
ethyl-3-ethoxypropionate	LOW	LOW

# **Bioaccumulative potential**

Ingredient	Bioaccumulation
LPG (liquefied petroleum gas)	LOW (LogKOW = 3.39)
toluene	LOW (BCF = 90)
acetone	LOW (BCF = 0.69)
ethyl-3-ethoxypropionate	LOW (LogKOW = 1.08)

#### Mobility in soil

Ingredient	Mobility
toluene	LOW (Log KOC = 268)
acetone	HIGH (Log KOC = 1.981)
ethyl-3-ethoxypropionate	LOW (Log KOC = 10)

# **SECTION 13 Disposal considerations**

#### Waste treatment methods

Product / Packaging disposal

- ▶ Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- ▶ Allow small quantities to evaporate.
- ▶ DO NOT incinerate or puncture aerosol cans.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

# **Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.


The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

# **SECTION 14 Transport information**

HAZCHEM

Not Applicable

# Labels Required



# Land transport (UN)

. , ,	
14.1. UN number or ID number	1950
14.2. UN proper shipping name	AEROSOLS
14.3. Transport hazard class(es)	Class 2.1

	Subsidiary Hazard Not Applicable		
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Environmentally hazardous		
14.6. Special precautions for user	Special provisions         63; 190; 277; 327; 344; 381           Limited quantity         1000ml		

# Air transport (ICAO-IATA / DGR)

14.1. UN number	1950			
14.2. UN proper shipping name	Aerosols, flammable			
	ICAO/IATA Class 2.1			
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable		
ciaco(co)	ERG Code	10L		
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Environmentally hazardous			
	Special provisions		A145 A167 A802	
	Cargo Only Packing Instructions		203	
	Cargo Only Maximum Qty / Pack		150 kg	
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		203	
	Passenger and Cargo Maximum Qty / Pack		75 kg	
	Passenger and Cargo Limited Quantity Packing Instructions		Y203	
	Passenger and Cargo Limited Ma	aximum Qty / Pack	30 kg G	

# Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1950		
14.2. UN proper shipping name	AEROSOLS		
14.3. Transport hazard	IMDG Class		2.1
class(es)	IMDG Subsidiary Ha	zard	Not Applicable
14.4. Packing group	Not Applicable		
14.5 Environmental hazard	Marine Pollutant		
	EMS Number F-D, S-U		
14.6. Special precautions for user	Special provisions	63 1	190 277 327 344 381 959
	Limited Quantities	1000	0 ml
	Limited Quantities	1000	0 ml

# 14.7. Maritime transport in bulk according to IMO instruments

# 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
LPG (liquefied petroleum gas)	Not Available
toluene	Not Available
acetone	Not Available
zinc phosphate	Not Available
ethyl-3-ethoxypropionate	Not Available

# 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
LPG (liquefied petroleum gas)	Not Available
toluene	Not Available
acetone	Not Available
zinc phosphate	Not Available
ethyl-3-ethoxypropionate	Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard	
HSR002515	Aerosols Flammable Group Standard 2020	

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

#### LPG (liquefied petroleum gas) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### toluene is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### acetone is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### zinc phosphate is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

New Zealand Workplace Exposure Standards (WES)

# ethyl-3-ethoxypropionate is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

#### **Additional Regulatory Information**

Not Applicable

#### **Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
2.1.2A	3 000 L (aggregate water capacity)	3 000 L (aggregate water capacity)

#### **Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

#### Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
2.1.2A				1L (aggregate water capacity)

# **Tracking Requirements**

Not Applicable

# **National Inventory Status**

National Inventory	Status			
Australia - AIIC / Australia Non-Industrial Use	Yes			
Canada - DSL	Yes			
Canada - NDSL	No (LPG (liquefied petroleum gas); toluene; acetone; ethyl-3-ethoxypropionate)			
China - IECSC	Yes			
Europe - EINEC / ELINCS / NLP	Yes			
Japan - ENCS	Yes			
Korea - KECI	Yes			
New Zealand - NZIoC	Yes			
Philippines - PICCS	Yes			
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'			
Taiwan - TCSI	Yes			
Mexico - INSQ	No (zinc phosphate)			
Vietnam - NCI	Yes			
Russia - FBEPH	Yes			
UAE - Control List (Banned/Restricted Substances)	No (LPG (liquefied petroleum gas); toluene; acetone; zinc phosphate; ethyl-3-ethoxypropionate)			
Legend:	Yes = All CAS declared ingredients are on the inventory  No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.			

# **SECTION 16 Other information**

Revision Date	03/02/2025
Initial Date	03/02/2025

# **SDS Version Summary**

Version	Date of Update	Sections Updated
2.1	03/02/2025	Hazards identification - Classification, Identification of the substance / mixture and of the company / undertaking - Synonyms

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- ▶ IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- ► TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ► NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

Disclaimer: This SDS was prepared by a third party for product identification purposes only and is not endorsed by or affiliated with the original brand owner.