

## Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: FG94 Meat Rail Lube Aerosol (Food Grade)

Product Code: 7294

**Uses:** Food grade lubricant for conveyor rails and transport chains.

Company: Chemz Limited

Address: 80 Rangitane Place

Whakatu, Hastings

Telephone: +64 6 877 9690
Email: info@chemz.co.nz

Emergency Phone Number: 0800 764 766 (0800 POISON) National Poison Centre 24 Hr

### Section 2 – HAZARDS IDENTIFICATION

#### Classification of the product

Considered a hazardous substance according to the Hazardous Substances (Hazard Classification) Notice 2020.

Classified as a dangerous goods for transport purposes.

#### **GHS Classifications:**

### **HSNO Classifications:**


Aerosol Category 1 2.1.2A Flammable aerosol Eye irritation Category 2 6.4A Irritating to the eye

STOT (Repeated exposure) Category 2 6.9B Harmful to human target organs or systems

Hazardous to Aquatic Environment (Chronic) Category 3 9.1C Harmful in the aquatic environment with long lasting effects







# **Hazard Statements:**

H222 Extremely flammable aerosol

H229 Pressurised container: May burst if heated

H319 Causes eye irritation

H373 May cause damage to organs through prolonged or repeated exposure

H412 Harmful to aquatic life with long lasting effects

### Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Hexanes	64742-49-0	30 - 60
EP Lubricant Grease FG (mineral oil)	8042-47-5	10 - 30
Hydrocarbon propellant (LPG - Propane, Butane)	68476-85-7	30 - 60
Non-hazardous ingredients		to 100

#### Section 4 - FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE or doctor.

Ref: FG94 Meat Rail Lube 7294 Date: 13.5.25 Supersedes: 18.4.20 Issue No: 4 Page 1 of 7 pages





**Skin contact:** IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice.

Inhalation: IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.

**Ingestion:** Not considered a normal route of entry. IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

Do NOT induce vomiting. Obtain immediate medical attention.

**Notes to physician:** Treat symptomatically and supportively. No specific antidote.

#### Section 5 - FIRE-FIGHTING MEASURES

**General fire hazards:** Pressurised container, extremely flammable aerosol.

Specific hazards: Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an

explosive mixture with air. Vapours can travel to a source of ignition and flash back. Contents may float

and be re-ignited on surface water.

Further advice: On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to

wear self-contained breathing apparatus if risk of exposure to products of combustion.

**Extinguishing media:** Use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective.

Do not discharge extinguishing waters into the aquatic environment. Do NOT use straight streams of

water.

**Protective equipment:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face

shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Firefighting instructions: In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move

containers from fire area if you can do so without risk. Runoff can cause environmental damage.

Hazchem Code: 2YE

### Section 6 – ACCIDENTAL RELEASE MEASURES

Minor spills: Clean up all spills immediately. Remove all sources of ignition. Wipe up with absorbent material. Avoid

breathing vapours and contact with skin and eyes. Wear protective clothing, gloves and safety glasses. Provide ventilation in workplace environment if necessary. If safe to do, damaged containers should be

placed in a container outdoors, away from all ignition sources.

Major spills: Evacuate the spill area and move upwind. Call the Fire Brigade. Remove all sources of ignition. No

smoking. May be violently or explosively reactive. Increase ventilation if possible. Wear breathing

apparatus and protective gloves.

If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal. Undamaged containers should be gathered and stored safely, away from

ignition sources.

#### Section 7 – HANDLING AND STORAGE

**Handling Precautions:** Read product label before use. Keep out of reach of children.

This product is highly flammable. Keep away from heat and open flames. Do not spray on an open flame or

other ignition source. Pressurised container: Do not pierce or burn, even after use. No smoking.

Use in a well-ventilated area. Avoid breathing spray or vapours. In confined areas, wear a respirator.

Wash hands with soap and water after handling.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool,

dry place. Do not store in basements or areas where vapours may accumulate. Keep away from heat,

sparks, and flame. Store away from incompatible materials. Store locked up.

Ref: FG94 Meat Rail Lube 7294 Date: 13.5.25 Supersedes: 18.4.20 Issue No: 4 Page 2 of 7 pages





### Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Limits:** No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m <sup>3</sup>	STEL, mg/m <sup>3</sup>	Cat/Notices
Hexanes	1,200	Not available	Not available
EP Lubricant Grease FG (Oil Mist, Mineral)	5	10	Not available
LPG (Liquefied petroleum gas)	1,800	Not available	Not available

(bio) - Exposure can also be estimated by biological monitoring.

#### **Emergency Limits (TEEL)**

#### **Temporary Emergency Exposure Limits**

Material	TEEL-1	TEEL-2	TEEL-3
Hexanes	1,000 ppm	11,000 ppm **	66,000 ppm***
EP Lubricant Grease FG (Oil Mist, Mineral)	140 mg/m <sup>3</sup>	1,500 mg/m <sup>3</sup>	8,900 mg/m <sup>3</sup>
LPG (Liquefied petroleum gas)	Not available	Not available	Not available

<sup>\*\*</sup> indicates value is 50 - 99% of LEL, \*\*\* indicates value is 100% or more of LEL

#### **Emergency Limits (IDLH)**

#### Immediately Dangerous To Life or Health (IDLH) Values

Material	Original IDLH	Revised IDLH
Hexanes	Not available	Not available
EP Lubricant Grease FG (Oil Mist, Mineral)	2,500 mg/m <sup>3</sup>	Not available
Butane	Not available	1,600 ppm (10% LEL)
Propane	Not available	2,100 ppm (10% LEL)

**Additional Information:** 

Wash hands before eating, drinking and smoking.

**Engineering Controls:** 

No controls generally required when handling small quantities. Use with adequate ventilation.

Larger quantities: General exhaust is adequate under normal operating conditions. Exhaust ventilation should be designed to prevent accumulation and recirculation in the workplace. Ventilation equipment and lighting should be explosion-resistant.

**Protective Equipment:** 

**Eye and face protection:** Safety glasses or goggles.

**Skin Protection:** No special equipment needed for minor exposure to small quantities. For moderate exposures wear general protective light weight latex gloves. For heavy exposures, wear chemical protective (PVC) and safety boots.

**Other Protection:** Protective clothing such as overalls, apron and boots are recommended for moderate or heavy use. Operators insulated from earth may develop static charges sufficient to ignite flammable gas/air mixtures. Avoid by wearing low resistivity outer material.

Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

**Respiratory Protection:** Where the concentration of gas/particulates in the breathing zone exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Use Type AX-P filter (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88)

The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator.

Cartridge performance is affected by humidity. Cartridges should be changed after 2 hours of continuous use unless the humidity is less than 75%, when cartridges can be used for 4 hours. Used cartridges should be discarded daily, regardless of the length of time used.

#### Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Ref: FG94 Meat Rail Lube 7294 Date: 13.5.25 Supersedes: 18.4.20 Issue No: 4 Page 3 of 7 pages



**Appearance**: Clear viscous liquid spray which foams up on application.

Odour: Hydrocarbon odour.

Odour Threshold: Not available.

pH: Not applicable.

Melting Point, °C: Not available.

Freezing Point, °C: Not available.

Initial Boiling Point, °C: 75 (base liquid)

**Boiling Point Range, °C:** 75 – 110 (base liquid)

Flash Point, °C: < 0 (propellant)

Flammability: Highly flammable liquid and vapour.

Explosion Limit, % v/v: LEL 1.2% UEL 9.5%

Vapour Pressure, kPa: 300 - 600

Vapour Density (Air = 1): > 1
Relative Density: 0.70

**Solubility:** Insoluble in water.

Partition Coefficient: Not available (n-octanol/water)

Autoignition Temp, °C: Not available.

Decomposition Temp, °C: Not available.

Kinematic Viscosity, mm²/s: Not available.

Particle Characteristics: Not available.

# Section 10 - STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

#### Section 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment: Information given is based on product testing, and/or similar products, and/or components.

Acute Oral Toxicity: LD<sub>50</sub> estimated to be >5,000 mg/kg (based on component mixture, excluding propellant).

Acute Dermal Toxicity: LD<sub>50</sub> estimated to be > 2,000 mg/kg (based on component mixture, excluding propellant).

**Acute Inhalation Toxicity:**  $LC_{50}$  estimated to be > 20 mg/L, Rat 4 hour (based on component mixture).

Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.

**Toxicity of Components:** 

Material	Toxicity	Irritation
Hexanes	Oral (rat) LD <sub>50</sub> > 4,500 mg/kg	Slight skin irritant.
	Dermal (rabbit) LD <sub>50</sub> > 1,900 mg/kg	
	Inhalation (rat) $LC_{50} > 4.42$ mg/L 4 hr	
EP Lubricant Grease FG	Oral (rat) LD <sub>50</sub> > 5,000 mg/kg	May irritate eyes.
	Dermal (rabbit) LD <sub>50</sub> > 2,000 mg/kg	
	Inhalation (rat) $LC_{50} > 5$ mg/L	
LPG ( butane, propane)	Inhalation (rat) LC <sub>50</sub> > 800,000 ppm (15 minutes)	Not a skin or eye irritant.

Not Available: Applies to data either not available or does not fill the criteria for classification.

**Skin Irritation:** Prolonged/repeated contact may cause defatting of the skin and dermatitis.

Ref: FG94 Meat Rail Lube 7294 Date: 13.5.25 Supersedes: 18.4.20 Issue No: 4 Page 4 of 7 pages



**Eye Irritation:** Spray may be irritating to the eye. Avoid contact with eyes.

**Inhalation:** Prolonged inhalation of spray may cause drowsiness or dizziness (narcotic).

**Respiratory Irritation:** Inhalation of vapours may cause irritation to the respiratory system.

**Sensitisation:** Not expected to be a contact or respiratory sensitiser.

Mutagenicity: Not expected to be mutagenic.

Carcinogenicity: Not expected to be carcinogenic.

**Reproductive toxicity:** Not expected to be a reproductive toxicant.

Specific Target Organ Toxicity: Harmful to human target organs (single exposure).

**STOT (Narcotic):** Inhalation may cause drowsiness or dizziness, particularly over long periods of exposure.

Repeated Dose Toxicity: Not available.

Additional Information: None of the components present in this material at concentrations equal to or greater than 0.1% are

listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

#### Section 12 – ECOTOXICITY INFORMATION

**Ecotoxicity:** For Hydrocarbons: log Kow 1, BCF ~ 1

Material	Test	Value	Source
Liquid Product	Not available	Not available	Not available
Hexanes	$LC_{50}$ Fish, 96 hr	4.1 mg/L	EchaChem
	$EC_{50}$ Crustacean, 48 hr	3.0 mg/L	EchaChem
	$EC_{50}$ Algae ,72 hr	> 1 mg/L	EchaChem
EP Lubricant Grease FG	EC <sub>50</sub> Daphnia, 48 hr	> 100 mg/L	Supplier
	EC <sub>50</sub> Algae, 72 hr	> 100 mg/L	Supplier
LPG ( butane, propane)	LC <sub>50</sub> Fish, 96 hr	24 mg/L	Supplier
	EC <sub>50</sub> Daphnia, 48 hr	14 mg/L	Supplier
	EC <sub>50</sub> Algae ,96 hr	7.7 mg/L	Supplier

**Persistence/degradability:** No data available for all ingredients (Air, Water, Soil).

Bioaccumulation Potential: No data available.

Mobility: No data available.

**Ecotoxicity:** Harmful to aquatic life with long lasting effects.

Other Adverse Effects: No data available.

#### Section 13 - DISPOSAL CONSIDERATIONS

Material Disposal: Product wastes are ecotoxic and should be disposed of in accordance with applicable regulations. Do not

dispose into the environment, in drains or in water courses. Waste product should not be allowed to

contaminate soil or water.

Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of

pressurised aerosols in landfills. Incineration in an authorised facility is suggested. \\


Container Disposal: Recycle empty container if possible or dispose in landfill. Product containers are also considered wastes

of the same class of the contents and should be disposed of in accordance with applicable regulations.

If it is a class 6, 8 or 9 it must be disposed by treating it so it is no longer a hazardous substance. If it contains components that are bioaccumulative and not rapidly degradable, it must be treated so that the

substance is no longer a hazardous substance.

Ref: FG94 Meat Rail Lube 7294 Date: 13.5.25 Supersedes: 18.4.20 Issue No: 4 Page 5 of 7 pages



Container Recycling: Recyclable metal - Recycle if possible. Packages which hazardous content have been appropriately

treated to remove residual contents may be recycled.

Workplace: Send empty cans to a metal recycler, approved aerosol recycler or commercial waste stream.

**Consumer:** Recycle if possible or place empty can in normal household waste stream.

#### Section 14 - TRANSPORT INFORMATION


**Transport:** Classified as a Dangerous Good for transport purposes.

Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7.

They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.

Proper Shipping Name: Aerosols
UN Number: 1950
Dangerous Goods Class: 2.1

Transport Labels Required: Class 2 Flammable (Land, Sea and Air)



Subsidiary Risk: Not applicable

Packing Group: Not applicable

Marine Pollutant: Yes

**EMS Number** F-D, S-U (UN 1950 Flammable aerosols)

**DG Segregation:** This product is classified as a Dangerous Goods. Consult the Land Transport Rule: Dangerous Goods 2005,

and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

# Section 15 - REGULATORY INFORMATION

EPA Approval Number: HSR002515 Aerosols (Flammable) Group Standard 2020.

EPA Hsno Controls: Refer to <a href="https://www.epa.govt.nz">www.epa.govt.nz</a> for information on Controls.

This substance is to be managed using the conditions specified in an applicable Group Standard.

Approved Handler: 2.1.2A - Required for quantities greater than 3,000 litres (aggregate water capacity).

Location Test Certificate: 2.1.2A - Required for quantities greater than 3,000 litres (aggregate water capacity).

**Tracking:** This substance is not a tracked substance.

Inventory Listing NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.

SDS regulations This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data

Sheets) Notice July 2017 (Consolidated 30 September 2022).

### Section 16 - OTHER INFORMATION

**Additional information** 

Personal Protective Equipment Guidelines: The recommendation for protective equipment contained is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final

selection of personal protective equipment is made.

Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Ref: FG94 Meat Rail Lube 7294 Date: 13.5.25 Supersedes: 18.4.20 Issue No: 4 Page 6 of 7 pages





Abbreviations CAS Chemical Abstract Service number

EMS Emergency Response Procedures for Ships Carrying Dangerous Goods

EPA Environmental Protection Agency

GHS Globally Harmonized System

IARC International Agency for Research on Cancer

IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC<sub>50</sub> Lethal Concentration, 50% / Median Lethal Concentration

LD<sub>50</sub> Lethal Dose, 50% / Median Lethal Dose

LEL Lower Explosion Limit

mg/m³ Milligrams per Cubic Metre

NZIoC New Zealand Inventory of Chemicals

N.O.S. Not otherwise specified
 OEL Occupational Exposure Limit
 PEL Permissible Exposure Limit
 STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

TLV Threshold Limit Value
TWA Time Weighted Average
UEL Upper Explosion Limit

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product. End of sds.

Ref: FG94 Meat Rail Lube 7294 Date: 13.5.25 Supersedes: 18.4.20 Issue No: 4 Page 7 of 7 pages