



Trusted Aerosol Performance

## SAFETY DATA SHEET

### Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** Grab It Belt Grip Aerosol 400ml  
**Product Code:** 7724  
**Uses:** Adhesive spray for indoor and outdoor transmission belts.  
**Company:** CChems Limited  
**Address:** 80 Rangitane Place  
Whakatu, Hastings  
**Telephone:** +64 6 877 9690  
**Email:** info@chemz.co.nz  
**Emergency Number 24 hr:** 0800 764 766 (0800 POISON) National Poison Centre

### Section 2 – HAZARDS IDENTIFICATION

#### Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ.  
Classified as a dangerous goods for transport purposes.

#### GHS Classifications:

Aerosol Category 1  
Skin irritation Category 2  
STOT (Repeated exposure) Category 3  
Aquatic toxicity (chronic) Category 2

#### HSNO Classifications:

2.1.2A Flammable aerosol  
6.3A Mildly irritating to the skin  
6.9B Harmful to human target organs or systems (narcotic)  
9.1B Ecotoxic in the aquatic environment with long lasting effects



**Signal Words:** Danger

#### Hazard Statements

H222 Extremely flammable aerosol  
H229 Pressurised container: May burst if heated  
H315 May cause skin irritation  
H336 May cause drowsiness or dizziness  
H411 Toxic to aquatic environment with long lasting effects

### Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Hexanes	64742-49-0	30 - 60
Hydrocarbon Propellant (LPG – Propane, Butane)	68476-85-7	30 - 60
Non Hazardous Ingredients	-	to 100

### Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.



Trusted Aerosol Performance

## SAFETY DATA SHEET

If exposed or if you feel unwell: Call a POISON CENTRE or doctor.

<b>Eye contact:</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
<b>Skin contact:</b>	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.
<b>Inhalation:</b>	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
<b>Ingestion:</b>	Not considered a normal route of entry. IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Obtain immediate medical attention.
<b>Notes to physician:</b>	Treat symptomatically and supportively. No specific antidote.

### Section 5 – FIRE-FIGHTING MEASURES

<b>General fire hazards:</b>	Pressurised container, extremely flammable aerosol.
<b>Specific hazards:</b>	Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. Contents may float and be re-ignited on surface water.
<b>Further advice:</b>	On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion.
<b>Extinguishing media:</b>	For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam.  For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the environment. Do NOT use straight streams of water.
<b>Protective equipment:</b>	Fire-fighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting instructions:</b>	In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers from fire area if you can do so without risk. Runoff can cause environmental damage.
<b>Hazchem Code:</b>	2YE

### Section 6 – ACCIDENTAL RELEASE MEASURES

<b>Minor spills:</b>	Clean up all spills immediately. Remove all sources of ignition. If safe to do, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Provide ventilation. Wash with water. Product is extremely slippery, especially when wet.
<b>Major spills:</b>	Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal.

### Section 7 – HANDLING AND STORAGE

<b>Handling Precautions:</b>	Read product label before use. Keep out of reach of children.  Caution: Stand back and keep hands and clothing away from moving belts. Restoration of pulling power may cause worn out belts to break. Grab It Belt Grip can be removed with Chemz Rapid Brake Clean #7856 or Chemz Electro Clean #7125.  This product is highly flammable. Keep away from heat and open flames. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even after use. No smoking. Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.  Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling.
<b>Storage:</b>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.



Trusted Aerosol Performance

## SAFETY DATA SHEET

### Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Limits:** No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m <sup>3</sup>	STEL, mg/m <sup>3</sup>
Hexanes	1,760	3,500
Hydrocarbon Propellant (Butane, Propane)	1,800	-

**Additional Information:** Wash hands before eating, drinking and smoking.

**Engineering Controls:** No controls generally required when handling small quantities. Use with adequate ventilation.  
Larger quantities: General exhaust is adequate under normal operating conditions. Exhaust ventilation should be designed to prevent accumulation and recirculation in the workplace. Ventilation equipment and lighting should be explosion-resistant.

**Protective Equipment:** General protective gloves are recommended. In an industrial environment: chemical protective gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

In case of inadequate ventilation, wear respiratory protection. If TWA is exceeded, wear an approved respirator with a type A filter.

### Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Clear liquid spray, characteristic odour.

**pH:** Not applicable.

**Vapour Density:** > 1 (Air =1)

**Vapour Pressure, kPa:** 300 - 600

**Boiling Point, °C:** About 60

**Melting Point, °C:** Not applicable.

**Specific Gravity:** About 0.7

**Flash Point, °C:** < 0 (propellant)

**Explosion Limit, % v/v:** LEL 1.2% UEL 9.5%

**Autoignition Temp, °C:** > 200

**Solubility:** Not soluble in water.

### Section 10 – STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

### Section 11 – TOXICOLOGICAL INFORMATION

**Basis for Assessment:** Information given is based on product testing, and/or similar products, and/or components.

**Acute Oral Toxicity:** LD<sub>50</sub> estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).

**Acute Dermal Toxicity:** LD<sub>50</sub> estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).

**Acute Inhalation Toxicity:** LC<sub>50</sub> estimated to be > 20 mg/L, Rat 4 hour (based on component mixture).

**Skin Irritation:** May cause slight skin irritation. Avoid contact with skin.

**Eye Irritation:** May cause eye irritation. Avoid contact with eyes.

**Inhalation:** May cause drowsiness or dizziness. Inhalation will cause narcotic effects.

**Sensitisation:** Not expected to be a sensitiser. May cause an allergic reaction in sensitive individuals.



Trusted Aerosol Performance

## SAFETY DATA SHEET

<b>Repeated Dose Toxicity:</b>	Repeated, prolonged exposure by inhalation may cause damage to organs.
<b>Mutagenicity:</b>	Not expected to be mutagenic.
<b>Carcinogenicity:</b>	Not expected to be carcinogenic.
<b>Reproductive toxicity:</b>	Not expected to be toxic to reproductive system.
<b>Additional Information:</b>	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as being carcinogens.



### Section 12 – ECOTOXICITY INFORMATION

<b>Ecotoxicity:</b>	Toxic to aquatic life with long lasting effects.
<b>Mobility:</b>	Low soil mobility.
<b>Persistence/degradability:</b>	Expected to biodegrade. Not expected to be persistent.
<b>Bioaccumulation Potential:</b>	May bioaccumulate.

### Section 13 – DISPOSAL CONSIDERATIONS

<b>Material Disposal:</b>	Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses.  Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.
<b>Container Disposal:</b>	Recycle empty container if possible or dispose in landfill. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.

### Section 14 – TRANSPORT INFORMATION

<b>Transport:</b>	Classified as a Dangerous Good for transport purposes.  Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7. They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.
<b>Proper Shipping Name:</b>	Aerosols
<b>UN Number:</b>	1950
<b>Dangerous Goods Class:</b>	2.1
<b>Transport Labels Required:</b>	Class 2 Flammable (Land, Sea and Air), EHS (Sea and Air)  Land, Sea, Air      Sea, Air   
<b>Subsidiary Risk:</b>	Not applicable
<b>Packing Group:</b>	Not applicable
<b>Marine Pollutant:</b>	Yes
<b>EMS Number</b>	F-D, S-U (UN 1950 Flammable aerosols)
<b>DG Segregation:</b>	This product is classified as a Dangerous Goods. Consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

### Section 15 – REGULATORY INFORMATION

<b>Inventory Listing</b>	NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.
--------------------------	--



Trusted Aerosol Performance

## SAFETY DATA SHEET

<b>SDS regulations</b>	This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2020.
<b>EPA Approval Number:</b>	HSR002515 Aerosols (Flammable) Group Standard 2020.
<b>EPA Hsno Controls:</b>	Refer to <a href="http://www.epa.govt.nz">www.epa.govt.nz</a> for information on Controls. This substance is to be managed using the conditions specified in an applicable Group Standard.

### Section 16 – OTHER INFORMATION

<b>Additional information</b>	<p>Personal Protective Equipment Guidelines: The recommendation for protective equipment contained is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.</p> <p>Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.</p>	
<b>Abbreviations</b>	CAS	Chemical Abstract Service number
	EMS	Emergency Response Procedures for Ships Carrying Dangerous Goods
	EPA	Environmental Protection Agency
	GHS	Globally Harmonized System
	IARC	International Agency for Research on Cancer
	IATA	International Air Transport Association
	IMDG	International Maritime Dangerous Goods
	LC <sub>50</sub>	Lethal Concentration, 50% / Median Lethal Concentration
	LD <sub>50</sub>	Lethal Dose, 50% / Median Lethal Dose
	LEL	Lower Explosion Limit
	mg/m <sup>3</sup>	Milligrams per Cubic Metre
	NZIoC	New Zealand Inventory of Chemicals
	N.O.S.	Not otherwise specified
	OEL	Occupational Exposure Limit
	PEL	Permissible Exposure Limit
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	TLV	Threshold Limit Value
	TWA	Time Weighted Average
	UEL	Upper Explosion Limit

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product. End of sds.