



Safety Data Sheet

Page 1 of 10

LOCTITE MR 5923 known as LOCTITE® AVIATION GASKET SEAL

SDS No. : 153785

V001.2

Revision: 04.08.2022

printing date: 06.08.2025

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: LOCTITE MR 5923 known as LOCTITE® AVIATION GASKET SEAL

Intended use: Sealant

Supplier:
Henkel New Zealand Ltd
2 Allens Rd
East Tamaki
Auckland, 2013
New Zealand
Phone: +64 (9) 272-6710

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

Classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

GHS Classification:

Hazard Class

Flammable liquids
Serious eye irritation
Skin sensitizer
Target Organ Systemic Toxicant -
Single exposure

Hazard Category

Category 2
Category 2A
Category 1
Category 3

Target organ

Central nervous system

Hazard pictogram:



Signal word:

Danger

Hazard statement(s):	H225 Highly flammable liquid and vapour. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary Statement(s):	
Prevention:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing mist/vapours. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description: Mixture
Type of preparation: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
rosin	8050-09-7	20- < 30 %
Propan-2-ol	67-63-0	20- < 30 %
Talc	14807-96-6	10- < 20 %
non hazardous ingredients~		30- <= 60 %

SECTION 4 FIRST AID MEASURES

Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Seek medical advice.
Skin:	Remove contaminated clothing and footwear. Rinse with running water and soap. Seek medical advice.
Eyes:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Inhalation:	Move to fresh air. Keep warm and in a quiet place. Seek medical advice.
First Aid facilities:	Eye wash and safety shower Normal washroom facilities
Medical attention and special treatment:	Treat symptomatically.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Improper extinguishing media:	High pressure waterjet.
Decomposition products in case of fire:	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide.
Particular danger in case of fire:	WARNING FLAMMABLE! Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
Special protective equipment for fire-fighters:	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.
Additional fire fighting advice:	In case of fire, keep containers cool with water spray.
Hazchem code:	•3YE

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Remove sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Wear appropriate personal protective equipment. Keep unprotected persons away.
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	Wipe up using absorbent material. Use noncombustible absorbent material such as sand. Store in a partly filled, closed container until disposal.

SECTION 7. HANDLING AND STORAGE**Precautions for safe handling:**

Keep away from heat, spark and flame.
Vapours should be extracted to avoid inhalation.
Use only in well-ventilated areas.
Avoid contact with eyes, skin and clothing.
Wear protective equipment.

Conditions for safe storage:

Store in a cool, dry, well-ventilated area.
Ground and bond metal containers for liquid transfer to avoid static sparks.
Do not store near sources of heat or ignition, or reactive materials.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Workplace exposure standards:**

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Ceiling	STEL (ppm)	STEL (mg/m3)
ISOPROPYL ALCOHOL 67-63-0		400	983	~	~	~
ISOPROPYL ALCOHOL		~	~	~	500	1,230
ISOPROPYL ALCOHOL		400	983	~	~	~
ISOPROPYL ALCOHOL		~	~	~	500	1,230
TALC (CONTAINING NO ASBESTOS FIBRES), RESPIRABLE DUST 14807-96-6	Respirable dust.		2	~	~	~

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Propan-2-ol 67-63-0	acetone	Blood	Sampling time: End of shift.	25 mg/l	DE BGW		
Propan-2-ol 67-63-0 [2-PROPANOL]	acetone	Urine	Sampling time: End of shift.	25 mg/l	DE BGW		

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Eye protection:

Wear protective glasses.

Skin protection:

Suitable protective clothing
The use of chemical resistant gloves such as Nitrile is recommended.
In circumstances where there is a potential for prolonged or repeated skin contact, the use of disposable gloves (polyethylene, natural rubber or equivalent ester-resistant material) is recommended.

Respiratory protection:

Do not inhale vapors and fumes.
Use only in well-ventilated areas.
If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	brown liquid
Odor:	Alcoholic
Specific gravity:	1.12
Boiling point:	> 82 °C (> 179.6 °F)
Flash point: (None)	15 °C (59 °F)
Evaporation rate:	7.7 (Ether = 1)
Vapor pressure: (; 20 °C (68 °F))	33 mm hg
Vapor density:	2.07 (Air = 1)
Density:	1.1 g/cm ³
Solubility in water:	Partially soluble
Viscosity (dynamic): (Brookfield; Instrument: RV; 25 °C (77 °F); speed of rotation: 5 min-1; Spindle No: 3; Method: ;; LCT STM 10; Viscosity Brookfield)	8,000 - 10,000 mPa.s
VOC content (2004/42/EC)	22.2 % (VOCV 814.018 VOC regulation CH)
VOC content: (2010/75/EC)	25 %

SECTION 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of temperature and pressure.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.
Incompatible materials:	Strong oxidizing agents. Acids.
Hazardous decomposition products:	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide.
Hazardous polymerization:	Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Health Effects:

Ingestion:

May cause dizziness, incoordination, headache, nausea, and vomiting.

Skin:

May cause mild skin irritation.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

May cause skin sensitization.

Eyes:

This product is irritating to the eyes.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Inhalation:

Vapours may cause drowsiness and dizziness.

Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
rosin 8050-09-7	LD50 LD50	2,800 mg/kg > 2,000 mg/kg	oral dermal		rat rat	not specified OECD Guideline 402 (Acute Dermal Toxicity)
Propan-2-ol 67-63-0	LD50 LD50	5,840 mg/kg 12,870 mg/kg	oral dermal		rat rabbit	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Talc 14807-96-6	LD50 LC50 LD50	> 5,000 mg/kg > 2.1 mg/l > 2,000 mg/kg	oral inhalation dermal	4 h	rat rat rat	OECD Guideline 423 (Acute Oral toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
rosin 8050-09-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Propan-2-ol 67-63-0	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Talc 14807-96-6	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
rosin 8050-09-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propan-2-ol 67-63-0	Category II		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Talc 14807-96-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Talc 14807-96-6	not sensitising	Guinea pig maximisa- tion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
rosin 8050-09-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay	with and without with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propan-2-ol 67-63-0	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Talc 14807-96-6	negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian cell transformation assay	with and without without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Talc 14807-96-6	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Propan-2-ol 67-63-0		inhalation: vapour	at least 104 w6 h/d, 5 d/w	rat	OECD Guideline 451 (Carcinogenicity Studies)
Talc 14807-96-6	NOAEL=100 mg/kg	oral: feed	101 d7 d/w	rat	equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)

SECTION 12. ECOLOGICAL INFORMATION

General ecological information:

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards., Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered.

Ecotoxicity:

Do not empty into drains / surface water / ground water.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
rosin 8050-09-7	LC50	Toxicity > Water solubility	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
rosin 8050-09-7	EL50	Toxicity > Water solubility	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
rosin 8050-09-7	EL50	Toxicity > Water solubility	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
rosin 8050-09-7	NOELR	Toxicity > Water solubility	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
rosin 8050-09-7	EC20	Toxicity > Water solubility	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Propan-2-ol 67-63-0	LC50	> 9,640 - 10,000 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	EC50	> 1,000 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	1,000 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Talc 14807-96-6	LC50	100,000 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	not specified

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
rosin 8050-09-7	readily biodegradable	aerobic	71 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
rosin 8050-09-7	> 3 - 6.2					OECD Guideline 117 (Partition Coefficient (n- octanol / water), HPLC Method)
Propan-2-ol 67-63-0	0.05					OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)

SECTION 13. DISPOSAL CONSIDERATIONS

- Waste disposal of product:** Dispose of according to regulations.
- Disposal for uncleaned package:** After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.
Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

Dangerous Goods information:

Land Transport:

Classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

Land Transport:

UN no.: 1866
Proper shipping name: RESIN SOLUTION
Class or division: 3
Packing group: II
Hazchem code: •3YE

Marine transport IMDG:

UN no.: 1866
Proper shipping name: RESIN SOLUTION
Class or division: 3
Packing group: II
EmS: F-E ,S-E
Seawater pollutant: -

Air transport IATA:

UN no.: 1866
Proper shipping name: Resin solution
Class or division: 3
Packing group: II
Packing instructions (passenger) 353
Packing instructions (cargo) 364

SECTION 15. REGULATORY INFORMATION

New Zealand regulatory information:

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

HSNO Approval Number: HSR002662

Approved Handler: Refer to the certified handler requirements in the Health and Safety at Work (Hazardous Substances) Regulations 2017

Site and Storage: Refer to the site and storage requirements for this Group Standard.
Refer to the HSNO controls for approved hazardous substances.

NZIoC: Compliant for NZIOC

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

STEL - Short term exposure limit
TWA - Time weighted average
HSNO - Hazardous Substances and New Organisms
GHS: Globally Harmonized System
CAS: Chemical Abstracts Service
LD 50: Lethal Dose 50%
LC 50: Lethal Concentration 50%
IMDG: International Maritime Dangerous Goods code
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

Reason for issue:

Reviewed SDS. Reissued with new date. involved chapters: 1 - 16

Date of previous issue:

25.07.2017

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.