



SCAN ME

Interconnectable Wireless Heat Alarm

Compatible with our range of Interconnectable Smoke Alarms sku: 7477 / Remote sku:7477-R

The PSL Interconnectable heat alarm provides battery-powered heat detection and alarm functions within a single unit. The technology provides reliable performance and low maintenance.

The interconnectable heat alarm is powered by a non-replaceable, long-life lithium-ion battery and does not require a mains supply.

The PSL Interconnectable Heat Alarms is suitable for general residential applications where a smoke alarm may result in unwanted activation. (Such as cooking areas/kitchens, parking garages, and areas with high dust levels and other airborne contaminants. The interconnectable alarm provides homeowners and installers with an easy-to-install, long-life solution for property protection applications.

Alarm hush time	9 min
Test Sounder	0.5s on / 0.5 s off
Test LED indicator	Flashing red every 1s
Operating Temp	(0~+55 oc)
Interconnection	no device limit 500m distance in free air
Operating humidity	(10~95)% RH, non-condensing



The PSL Interconnectable Alarms comply with the changes to the NZ Building Code In Relation to Smoke Alarms which came into effect on Nov 2023

www.pslfireandsafety.co.nz

+64 9 818 8048
sales@pslfireandsafety.co.nz



Quality Management System Certification
ISO 9001:2015



Environmental Management System Certification
ISO 14001:2015



Occupational Health and Safety Management System Certification
ISO 45001:2018